Theses and Dissertations | 1. Thesis and Dissertation Collection, all items

2000

Validation of the mine impact burial model using experimental data.

Smith, Timothy Brian

Monterey, California. Naval Postgraduate School

NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

VALIDATION OF THE MINE IMPACT BURIAL MODEL USING EXPERIMENTAL DATA

by

Timothy Brian Smith

September 2000

Thesis Advisor: Peter C. Chu
Second Reader: Steve Haeger

REPORT DOCUMENTATION PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE September 2000	3. REPORT TYPE AND DATES COVERED Master's Thesis

4. TITLE AND SUBTITLE	5. FUNDING NUMBERS
VALIDATION OF THE MINE IMPACT BURIAL MODEL USING EXPERIMENTAL DATA	

6. AUTHOR(S)
Smith, Timothy Brian

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Postgraduate School Monterey, CA 93943-5000	8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) NAVOCEANO, Stennis Space Center, MS 39522-5001	10. SPONSORING / MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.

12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.	12b. DISTRIBUTION CODE

13. ABSTRACT (maximum 200 words)

The Navy's Impact Burial Prediction Model creates a two-dimensional time history of a bottom mine as it falls through air, water, and sediment. The output of the model is the predicted burial depth of the mine in the sediment in meters, as well as height, area, and volume protruding. Model input consists of environmental parameters and mine characteristics, as well as parameters describing the mine's release. The model user seldom knows many of these parameters, and those that are known may be of questionable precision.

In order to run a realistic validation of the model, an experiment was conducted using a simulated mine and carefully controlled observations while simultaneously taking gravity cores. The model was then run and calculated results were compared to observed. Final results showed the model tended to over predict burial depth by an order of magnitude due to a lack of sensitivity to hydrodynamic effects in the water column.

14. SUBJECT TERMS Modeling and Simulation, Meteorology and Oceanography, METOC, Mine Impact Burial Prediction, Bottom Mine, Decision making	15. NUMBER OF PAGES 190
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFI- CATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL

VALIDATION OF THE MINE IMPACT BURIAL MODEL USING EXPERIMENTAL DATA

Timothy Brian Smith
Lieutenant, United States Navy
B.S., Oregon State University, Corvallis Oregon, 1993

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN METEOROLOGY AND PHYSICAL OCEANOGRAPHY

from the

NAVAL POSTGRADUATE SCHOOL
September 2000

ABSTRACT

The Navy's Impact Burial Prediction Model creates a two-dimensional time history of a bottom mine as it falls through air, water, and sediment. The output of the model is the predicted burial depth of the mine in the sediment in meters, as well as height, area and volume protruding. Model input consists of environmental parameters and mine characteristics, as well as parameters describing the mine's release. The model user seldom knows many of these parameters, and those that are known may be of questionable precision.

In order to run a realistic validation of the model, an experiment was conducted using a simulated mine and carefully controlled observations while simultaneously taking gravity cores. The model was then run and calculated results were compared to observed.

Final results showed the model tended to over predict burial depth by an order of magnitude due to a lack of sensitivity to hydrodynamic effects in the water column.

TABLE OF CONTENTS

LIST OF FIGURES

LIST OF TABLES

TABLE OF SYMBOLS

Λ_s	=	Kinematic viscosity of the sediment
Λ_w	=	Water viscosity
Δ_s	=	Density of the sediment
$\mathbf{F_b}$	=	Buoyancy Force
$\mathbf{F_c}$	=	Compressive force
$\mathbf{F_d}$	=	Drag Force
$\mathbf{F_s}$	=	Shear force
$\mathbf{F_{w,a}}$	=	Force due to weight of air on mine
h	=	Penetration depth (cm)
K	=	Constant depending on cone angle
$\mathbf{M_r}$	=	Resultant Mass
Q	=	Weight (grams)
ρ	=	Density (kg/m^3)
V	=	Velocity
s	=	Undrained shear strength
S_u	=	Shear strength

ACKNOWLEDGEMENT

I. INTRODUCTION

Since the conclusion of the cold war, emphasis has been shifted from blue-water, open ocean battle tactics to littoral warfare. It is in this arena that mine warfare has become an all-important issue. Mine warfare is one of most cost efficient ways to protect critical waterways and inflict serious damage upon a fleet. The fear inflicted upon an enemy fleet after knowledge of the presence of mines is a psychological bonus that enhances their effectiveness as a weapon. Many mines are of the same design as their counterparts from thirty or forty years ago. Their simplicity, effectiveness, and cost efficiency make them an appealing weapon for third world countries.

There are hundreds of variations of mines and they are triggered various ways. In 1776, an American, David Bushnell, who is also recognized as the inventor of America's first submarine, invented the first known sea mine. Bushnell's mine was a simple watertight wooden keg, loaded with gunpowder, which hung from a float and, at that time, was called a torpedo. In 1777, under orders from General Washington, a number of the kegs were set adrift by Bushnell in an attempt to destroy a fleet of British warships anchored in the Delaware River off Philadelphia. The attempt failed. But the naval mine has since - through the American Civil War, World Wars I and II, and the Korean and Southeast Asian Conflicts - gained a reputation as one of the Navy's least costly, yet most effective, offensive and defensive weapons.

Modern times have not changed the value placed on mines. Although technology has improved and new and more effective mines have been invented, many third world countries still employ mines of the simplest design. Mine detection capability is now in the spotlight.

Mines are deployed one of three ways: aircraft, sea surface, or subsurface. Mines will float on the surface through inherent buoyancy, float just below the surface using some sort of anchoring mechanism or lodge themselves in the sea bottom. They can detonate by contact, disruption of a magnetic field, or by acoustic detection. For the mines which imbed themselves in the sea floor, the sensitivity of the mine trigger is directly proportional to the amount of the mine protruding from the sea floor. Because of this, it is important to be able to predict the burial depth of the mine depending upon deployment platform, sediment type and oceanographic conditions.

Chu et al. (2000) reviewed the current status of current numerical models for simulating the mine burial process and constituting the viable means for burial depth prediction. These models provided some information for clearing an area of mines. However, the Impact Burial (IB) model was developed to determine the depth at which the mine comes to rest in the sediment upon impact and at which only the momentum equations of the mine gravity center and considered (Arnone and Bowen, 1980). The IB model was designed to create a two-dimensional time history of a cylindrical mine as it falls through air, water, and sediment phases (Figure 1). The burial depth of the mine in the marine sediment is then calculated from the mine's velocity on contact with the sediment and the sediment characteristics. Several revisions have been made to the model to refine the physics and allow for more realistic geometry and more extensive input from the user. Most notable are the changes made by Satkowiak (1987) and Hurst (1991). Other revisions involved translating to newer computer language. Currently, the model allows the user to input nearly any value for each environmental parameter.

Figure 1. The trajectory of a cylindrical mine as it falls through three phases: air, water, and sediment. Labels are parameters used by the model to calculate the velocity, attitude, and burial depth of the mine. (From Arnone and Bowen, 1980)

The most popular IB model is IMPACT25. The altitude from which the mine is released determines the velocity and attitude of the mine as it reaches the air-water interface. IMPACT25 simulates one of the two kinds of mine motion: (1) falling downward without any rotation around its gravity center, and (2) "tumbling" with a constant rate of rotation. The attitude of the mine upon reaching the water is impacted greatly by the release altitude. Although not accounted for in the model, this rotation rate may be caused or affected by wind.

In the water phase, this rotation rate is damped significantly. However, it still has a great effect on the angle the mine makes with the sediment upon impact. Currents may affect the rotation rate in the model, but again are not accounted for in the model. The water depth only has an effect on impact velocity if it is less than that required for the

mine to reach terminal velocity, the velocity at which the deceleration due to frictional drag is equal to the acceleration from gravity. The velocity at which this equilibrium is reached is a function of the weight of the mine. Since mines are laid in shipping channels almost exclusively, one may assume that water depths in excess of that required for a mine to reach terminal velocity are the norm. Water temperature has an effect on the viscosity of seawater, and hence increases the drag of the seawater on the mine.

Data input for the IMPACT25 model can be split into two categories. The first category is rudimentary deployment and oceanographic water column data. The second category is more detailed sediment data. Penetration depth predictability is going to depend directly on impact velocity, and sediment density and shear strength values. The model puts sufficient emphasis in the utilization of sediment parameters but idealistic conditions for predicting impact velocity.

The output of the model is in question due the instability of ocean sediment. Until this experiment was conducted, dated sediment values were used when running the code that led to skepticism in the validity of it's output. Changes in the water column due to turbulence and currents above an impact area have a significant effect on sediment characteristics in the upper layers. These same changes in the water column have a direct effect on the impact velocity and orientation and are not addressed by the model. Sensitivity studies (Taber 1999; Chu et al. 2000) indicate the importance of the environment, especially on the bottom shear strength in the mine impact burial.

Before transferring the IMPACT25 model for naval operation use, we should verify the model using synchronous mine impact burial and environmental data. Unfortunately, it is very hard to find such a data set. The current data sets are either the

4

mine data or the environmental data only. It is therefore a high priority to collect the data for the evaluation of the IMPACT25 model.

This thesis includes three parts: (1) collecting synchronous mine impact burial and environmental data through the Mine Impact Burial Experiment (MIBEX) at Monterey Bay, (2) analyzing the real-time environmental data collected at the Rapid environmental Assessment Laboratory (REAL), and (3) evaluating IMPACT25 using the MIBEX data.

THIS PAGE INTENTIONALLY LEFT BLANK

II. ENVIRONMENT OF THE MONTEREY BAY

A. GEOLOGY AND STRUCTURE

The experiment was conducted in the Monterey Bay National Marine Sanctuary (MBNMS) off the central coast of California. The location was chosen because of its accessibility and the oceanographic data collection capability already in place. The MBNMS spans nearly 10,000 km² in the central California region, and extends offshore an average distance of approximately 50 km (a maximum distance of nearly 100 km in the Monterey Bay area and a minimum distance of 15 km off Partington Point) between the Farallon Islands in the north and Morro Bay in the south (Figure 2).

Figure 2. The Monterey Bay National Marine Sanctuary

It contains one of the world's most geologically diverse and complex seafloors and continental margins. The MBNMS is located on a plate boundary, which separates the North American Plate from the Pacific Plate, and is marked by the San Andreas fault system. This is an active tectonic region with common occurrences of earthquakes, submarine landslides, turbidity currents, flood discharges and coastal erosion. It is also a region of extensive natural and economic resources.

Coastal topography varies greatly, encompassing steep bluffs with flat-topped terraces and pocket beaches to the north; large sandy beaches bordered by cliff and large dune fields mid-sanctuary; and predominately steep, rocky cliffs to the south. Low- to high-relief mountain ranges and broad, flat-floored valleys are prevalent farther inland.

The Santa Cruz and Gabilan mountain ranges dominate the topography in the northern and central half of the region. Two major rivers (San Lorenzo and Pajaro Rivers) and a major creek (Scott Creek) enter Monterey Bay from these highlands through well-defined valleys (Figure 2). Elkhorn Slough, an old river estuary that today is occupied only by tidal salt marshes, extends inland from Moss Landing for more than 10 km. The broad, extensive Salinas Valley and the northern Santa Lucia Range are the dominant topographic features in the southern half of the region; the Salinas River is the major drainage system (Figure 2). South of Monterey, the west flank of the Santa Lucia Range drops abruptly into the ocean. Here, the valleys of the Carmel and Little Sur Rivers are dominant topographic features. From Point Sur to Morro Bay many streams and creeks drain the southern Santa Lucias and cut the steep western face of the mountain range.

The MBNMS is located along the active transform boundary (the San Andreas fault system) separating the Pacific Plate from the North American Plate. Here the fault system is over 100 km wide and incorporates faults in the offshore, including those of the Palo Colorado-San Gregorio and Monterey Bay fault zones. These fault zones are seismically active, and in many places offset the seafloor or Quaternary sedimentary rocks. A paleo-subduction zone occurs along the MBNMS western boundary; the fossil thrust faults in this zone appear to control the structure at the base of the continental slope.

Most of the northern and central parts of the MBNMS lie within the Salinian block. It is composed of allochthonous (i.e. transported to local region) Cretaceous granitic basement material, primarily overlain with Neogene marine sedimentary units; it has been tectonically slivered into its present position. This block has been carried upon the Pacific Plate as the plate moves northward, slipping along the San Andreas fault for about the past 21 million years.

In the Monterey Bay region, the plate boundary between the North American and Pacific plates is comprised of the San Andreas fault system, consisting of the Hayward-Calaveras and San Andreas fault zones on land, and the offshore Palo Colorado-San Gregorio fault zones. The Palo Colorado-San Gregorio is the major active fault zone within the MBNMS. It is a right-lateral strike-slip fault zone oriented generally north-south, comprised of two or more parallel and fairly continuous fault segments that extend at least 100 km from Point Año Nuevo in the north to Garrapata Beach (10 km north of Point Sur). The amount of right-lateral offset along this fault zone has been measured by different methods and at several locations; offset varies from 80-90 km to as much as 150

km.

The Monterey Bay fault zone is a wide (~10 km), en echelon (i.e. composed of short, discontinuous, offset, roughly parallel faults) formation comprised of many fault segments ranging from 5 km or less up to 15 km in length. The Monterey Bay fault zone is either truncated or merges with the San Gregorio fault segment of the Palo Colorado-San Gregorio fault zone.

Monterey Canyon, the most dramatic submarine feature of the sanctuary, rivals the Grand Canyon in relief and topographic complexity. Monterey Canyon ranks among the larger canyons of the world and has a richness of life that exceeds that of most land and marine areas. The marine sanctuary, about 7,500 square kilometers of ocean and seafloor off central California, is home to a rich diversity of marine life. More than 30 species of marine mammals live in or visit the Bay, making it one of the largest collections in the northern hemisphere. For example, Bairds Beaked Whale navigates the canyon to make infrequent surface visits to the Bay. The sanctuary is rich in marine life because nutrient-enriched seawater upwells along the steep margin from deeper, colder waters.

Sediments derived from land accumulate in the marine environment, often at a temporary location awaiting a large storm, strong currents, or a quick shake from an earthquake to send them cascading down the canyon. The region is tectonically active, a fact underscored by the 7.0-magnitude Loma Prieta earthquake in 1989. Much has been learned from that event, including indications that the style of faulting may be significantly different than previously thought. Such differences have implications for how rocks move and react to shock waves, which, in turn, influence the size of

earthquakes. Further studies are needed to determine how these rocks are packaged, how the packages move, and what effect that movement has on the seafloor and adjacent coast.

Sediments deposited on the shelf are affected by winter storms, which resuspend particles and transport them to new locations. For example, giant landslides and currents of turbid materials occur in Monterey Canyon when waves or earthquakes destabilize huge piles of sediment at the head of the canyon. These slides and flows are well documented, but the extent of movement is not well known. Recent mass movements of sediments have moved electronic instruments on the seafloor miles down the canyon. Movement of sediments along the coast and their ultimate accumulation more than 300 kilometers from the shore are topics of study requiring a long-term research commitment.

B. OCEANOGRAPHY

The oceanography of the Monterey Bay National Marine Sanctuary (MBNMS), including Monterey Bay and the coastal area between the Gulf of the Farallones and Point Piedras Blancas, is closely tied to processes of the California Current. The California Current is an eastern boundary current that has been characterized generally as a broad, shallow, slow southward moving current exhibiting high spatial and temporal variability. The California Current is the eastward portion of the clockwise North Pacific Gyre and transports low salinity, cool water equatorward. Associated with the coastal surface flow is a poleward undercurrent, the California Undercurrent. Even though the California Current is one of the most-studied oceanographic features in the oceans, it is difficult to predict at any particular instant the location of its velocity core, its speed, or

direction. Indeed, at various locations observers might characterize the current as south flowing (as it often is in offshore regions), westward flowing (as is frequently observed in a coastal jet near Point Reyes), or eastward flowing (as found in the southern regions of such jets). At times, principally in winter, the nearshore current flows northward.

The California Current can be divided into three regions (based on the seasonal amplitude variation and standard deviation of dynamic height): an offshore oceanic regime, a coastal regime and an intervening transition zone. This transition zone lies approximately 200-300 km west of Point Sur. Geostrophic speeds in the core of the California Current may approach 25 cm/s, but generally are 5 to 10 cm/s (0.1 to 0.2 knots). Infrared AVHRR (Advanced Very High Resolution Radiometer) satellite images clearly show surface effects of such eddies and the presence of coastal jets (Figure 3). The core of the California Current lies in the salinity minimum about 300 km offshore of Point Sur, within the transition zone, and is not associated generally with a thermal gradient. This makes location of the California Current difficult from infrared imagery (Figure 3). The low salinity waters derive generally from the low salinities in the Gulf of Alaska and more locally from the Columbia River discharge and outflow from the Sacramento and San Joaquin Rivers through the mouth of San Francisco Bay.

The California Current is richly populated with semi-stationary jets and eddies. Satellite imagery (Figure 3 and Figure 4) has shown cold filaments on the order of 50 km wide to extend several hundred km offshore. The importance of these features, which represent the highly variable oceanographic "weather" of the California Current, lies in their offshore transport of cool, nutrient-rich upwelled water. This extends the effects of nearshore upwelling which is confined to a band about 50 km wide to several hundred

km. Cross-shore velocities may reach 1 m/s which is an order of magnitude greater than characteristic speeds of the California Current core. In what are called "squirts," the flow

Figure 3. AVHRR infra-red image of sea surface temperature along the central California Coast. 12 June 1993

may be directed offshore, and where the "squirt" dissipates elongated "hammerhead" features evolve (Figure 3). Between mesoscale eddies, the flow is directed offshore north of cyclonic eddies and onshore south of them. A jet may be found off Point Sur that transports cool, upwelled waters offshore 100 km. The "San Francisco Eddy" is a semi-permanent cyclonic eddy northwest of Monterey Bay, while other observations describe

anti-cyclonic eddies in this region. Current meter measurements and estimated geostrophic flow in an anti-cyclonic eddy southeast of Monterey Bay. Between that eddy and a cyclonic eddy just north of it strong onshore geostrophic flow was observed.

Figure 4. AVHRR infra-red satellite image of sea surface temperature 28 April 1993. This image is not typical of temperature distributions in the California Current.

The surface and intermediate depth water masses in the MBNMS are a mixture of Pacific Subarctic water having low salinity and cool temperatures and the warmer, saltier Pacific Equatorial water. Nearshore surface temperatures vary from 8°C during winter and early spring to 17°C during fall. Nearshore surface salinities vary from 34.0 psu (practical salinity units) when upwelling is strong to 33.2 psu otherwise. Streams and

rivers have large local effects on salinity, but even during flood conditions the salinity of Monterey Bay surface waters does not fall below 31 psu (Figure 5).

Figure 5. Near-surface salinity distributions a) 14-15 Dec. 1972; b) 25-26 Jan 1973; c) 22-23 Feb 1973; d) 22-23 Mar 1973. (From Broenkow and Smethie 1978).

An analysis of surface waters in the California Current 150 km offshore of Monterey Bay, showed from harmonic analysis that the seasonal variation of temperature and salinity were 12.2°C to 15.5°C and 33.1 to 33.3 psu. Both temperature and salinity maxima are reached typically in September-October, while minimum temperature occurred in February-March and minimum salinity in December-January. At a station 10 km south of Monterey Bay off Point Sur, temperature varied from 11.1°C in May to

13.8°C in November and salinity from 33.4 in January to 33.6 in July-August. Variance about the regression lines was about 1°C and 0.2 psu.

The vertical distributions of salinity, temperature, dissolved oxygen and inorganic nutrients were systematically characterized by the California Cooperative Fisheries Investigations. Monthly or biweekly hydrographic stations were occupied at Hopkins Marine Station CalCOFI Station H3 about halfway between Point Pinos and Point Santa Cruz where the canyon depth is about 900 m. The near-surface halocline is accompanied by a similar thermocline. It is noted that in spring and summer, the mixed layer is often absent. Conditions similar to those offshore are found at the H3 entrance to Monterey Bay so that mid-Bay waters are only slightly altered by localized warming and nutrient assimilation. The oxygen minimum, which is prevalent throughout the North Pacific, is found near 600 m where oxygen concentrations are less than 0.5 ml/liter or 20 mmoles/kg and saturation levels are less than 10%.

Within the coastal regime, sea surface flow undergoes a seasonal reversal. During the late fall and winter the direction is primarily poleward while equatorward flow dominates during the spring and summer. The equatorward flow is coupled with the intensification of northwesterly winds that generally parallel the central California coastline. Wind intensity is proportional to the barometric pressure difference between the North Pacific High and the thermal low pressure centered in southern Nevada and California. This pressure gradient begins to form and strengthen in the spring. The sudden strengthening of the northwesterly winds, usually in March- May, may result in the "spring transition" in which upwelling commences and local sea surface temperatures fall by as much as 5°C within a few days. Surface waters are advected offshore, and

equatorward geostrophic flow is established after baroclinic adjustment. During late fall, the North Pacific High weakens and migrates southward and the thermal low disappears. The surface flow reverses to poleward and can be regarded as the surface signature of the California Undercurrent, although some investigators refer to this poleward current as the Davidson Current. The timing and phasing of these coupled oceanographic and meteorological processes has been extensively studied along the California coast north of Pt Reyes.

Locally the alongshore wind stress is persistently from the north and does not reverse direction, while along the Mendocino coast and further north, the direction of the wind stress changes seasonally. During late fall and winter, winds become more variable as storms periodically reverse the wind direction. Maximum seasonal wind stress at 35°N occurs in May-June where at 39°N the maximum wind stress occurs in July. This seasonal variation in wind patterns has several effects. When winds are strongly from the northwest (between March and September along the central California coast, the wind-driven Ekman transport of the waters between the surface and about 50 m has an offshore component. The sea surface is lowest along the coast, and tilts upward by about 20 cm across the width of the California Current (1000 km). Surface waters moved seaward are replaced by deeper upwelled waters, which flow shoreward and upward beneath the Ekman layer. The isopleths of density, temperature, salinity and other tracers tilt upward by approximately 50 m in 100 km and locally by as much as 100 m in 20 km. Upwelling is the combined process of the vertical movement of the pycnocline and inclined flow along it. Upwelling speeds may reach 1 m/day or greater under favorable wind conditions

and from depths as great as 200 m. The seasonal rise and fall of temperature isopleths is observed to 500 m.

III. MIBEX AT THE MONTEREY BAY

A. PREPARATION

The original concept for the experiment was to validate the IMPACT25 by pushing a 55-gallon drum off the end of Fisherman's Wharf Pier Number two (Figure 6). This would accomplish two major tasks. First, it would check to see how the physics of the model worked with a real world situation. Second, it would provide directly measured sediment data possible to input into the model since gravity cores would be taken simultaneously with the drops. This second task would be critical because the underwater environment is incredibly dynamic and the code calls for input of sediment characteristics.

Figure 6. The initial experiment site.

machines and therefore was judged unsuitable for any type of mine penetration. Its depth and accessibility to crane operations would have made it a good location for multiple drops.

On February 7, 2000, a sedimentologist from the Monterey Bay Aquarium Research Institute (MBARI) named Charlie Paull was contacted to inquire on recommendations for an alternate site in Monterey Bay. He confirmed that Monterey Harbor would be a poor choice due to the hardness of the bottom and suggested going to an area approximately one quarter mile offshore from Fort Ord's now defunct Officer's Club. After numerous reviews, this site was also abandoned due to logistics complications pertaining to oceanographic data measuring equipment desired in the experiment.

On April 17, 2000, a discussion was held with Rob Wynand of the Naval Postgraduate School and it was decided that a survey would be conducted at the site of the Monterey Inner Shelf Observatory (MISO) off of Del Monte Beach in Monterey Bay. After an exploratory dive, the bottom composition was determined to be adequate for the experiment. The bottom was found to be composed of "sandy ledges" and the water depth was approximately 12 meters (similar to real world bottom mining environments).

Following this meeting, Captain Lee Bradford of MBARI was contacted for information on research vessels at our disposal. The platform we used had to be capable of safely releasing and retrieving a 650 pound barrel multiple times from the bottom in 12 meters of water. The Research Vessel John Martin (Figure 7) was selected and 23 May was scheduled to conduct the experiment.

Figure 7. R/V John Martin, MBARI

In conjunction with Captain Bradford's meeting, Jon Heine was contacted and solicited to be the dive supervisor for the experiment. It was ascertained that a minimum of four divers would be needed to safely go up and down the 12-meter depth 20 times. Heine's divers would also take the gravity cores and film the barrel entry and other pertinent underwater evolutions.

The next task was contacting the United States Geological Survey (USGS) office to determine the proper procedure for taking and analyzing gravity cores. A geologist named Homa Lee volunteered to provide assistance on May 31, 2000 and offered the use of the USGS freezer to store the gravity cores after the experiment. On the morning of May 22, 2000, Andy Andersen of the Oceanography department at the Naval Postgraduate School (NPS) contacted the Environmental Health office and secured a 55 gallon drum which was to be modeled as the "mine." Although "ribbed," it was assumed the symmetrical design would have little effect on hydrodynamics in the water column. (Figure 8)

Figure 8. Andy Andersen getting the "mine" ready. (May 22, 2000)

The mine was to be filled with sand to give it a uniform density. This sand was obtained from the beach adjacent to the NPS Oceanography Laboratory near Del Monte Beach in Monterey Bay.

Prior to this happening, gravity cores had to be fashioned. Two and one-half inch polycarbonate piping and rubber stoppers were ordered. The polycarbonate piping was cut into eight, three-foot lengths and four, two-foot lengths. These were carried in a special rack designed to transport the sediment intact to the USGS. (Figure 9)

On the afternoon of May 22, 2000, the R/V John Martin was loaded with the mine, gravity cores and dive equipment. Captain Lee Bradford supplied a seaforth quick-release to be used when dropping the barrel. This quick release could be easily fastened and released by a diver in the water, therefore providing the greatest margin of safety for the divers.

Figure 9. Gravity Cores in Rack

B. EXPERIMENT

On May 23, 2000, the R/V John Martin got underway at 0630. The team was on location and in the water by 0805. After an extensive safety discussion, it was decided that the barrel/mine would be released while touching the surface. This would be to eliminate any chance of inertial effects caused by uneven introduction into the air-sea interface. This also set the initial velocity parameter in the code to zero.

The barrel was to be released 20 times, although only seventeen drops were actually made because of diver limitations. The diver would snap the quick-release shackle on the barrel and then dive down to conduct measurements. The average depth of the water was 13 meters. Since it was uncertain the path the barrel would follow, both the releasing diver and a second safety diver would stay on the surface until after the barrel had dropped. Once reaching the bottom, one diver would take penetration measurements using a meter stick marked at millimeter increments while the other would take a gravity core.

After 17 drops, the divers began to run out of air and results were not varying greatly so the decision was made to end the experiment. Upon return to the Monterey Bay Aquarium Research Institute, the gravity cores were taken immediately to the USGS

Laboratories in Menlo Park, California where they were refrigerated until the analysis could be performed on May 31 – June 1, 2000.

IV. SEDIMENT DATA ANALYSIS

A. GRAVITY CORE ANALYSIS

Analysis of the gravity cores was begun on May 31, 2000 at the USGS Laboratories in Menlo Park, California with the aid of a graduate student, Priscilla Barnes. The gravity cores were sliced into two-centimeter segments to a depth of ten centimeters, and then sliced into four-centimeter segments. A Fall Cone Apparatus (Model G-200) was used to determine sediment shear strength. (Figure 10)

In the test, it is assumed that the shear strength of sediment at constant penetration of a cone is directly proportional to the weight of the cone, and the relation between undrained shear strength s and the penetration h of a cone of weight Q is given by:

$$s = K \frac{Q}{h^2}$$

where K is a constant which depends mainly on the angle of the cone, but is also influenced by the density of the clay/sediment.

Four different cones are used with this instrument, each one having the following measurement range:

Weight	Apex-Angle	Penetration in mm	Undrained shear strength in $\frac{t}{m^2}$
400 gr.	30°	4.0 – 15.0	25 – 1.8
100 gr.	30°	5.0 – 15.0	4 – 0.45
60 gr.	60°	5.0 – 15.0	0.6 – 0.067
10 gr.	60°	5.0 – 20.0	0.10 – 0.0063

Table 1. Measuring range of Fall Cone Apparatus Model G – 200.

The cones are suspended from a permanent magnet. By pressing a knob, the magnet is moved so that the magnetic field is broken momentarily, and the cone is released.

Figure 10. Fall Cone Apparatus Model G - 200

Measurements are taken of penetration depth and the evolution is repeated five times per sediment slice. These values are then averaged and correlated with a table which gives shear strength.

B. SEDIMENT PROFILES

Previous studies (Taber 1999; Chu et al. 2000a,b) showed that the sediment parameters are the most critical element in determining how deep the mine was buried when it came to rest. Sensitivity to the alteration of sediment density and shear strength was tested using six sediment profiles including three profiles from Sydney Harbor (Mulhearn, 1993) and three profiles available for selection in the IB model. The profiles included in the model are called simply "softsed", "medsed", and "hardsed" and do not clearly correspond to specific sediment types.

During the MIBEX at the Monterey Bay, we obtained 17 gravity cores. Sediment density was observed to generally increase until approximately 6-9 cm below the surface after which it would decrease (Figures 11-13). Sediment shear strength tended to increase as depth increased (Figures 14-16).

26

Figure 11. Density Vs. Depth For Cores 1-3, 5.

Figure 12. Density Vs. Depth for Cores 6-9.

28

Figure 13. Density Vs. Depth for Cores 10-12.

Figure 14. Shear Strength Vs. Depth for Cores 1-3, and 5.

Figure 15. Shear Strength Vs. Depth for Cores 6-9.

Figure 16. Shear Strength Vs. Depth for Cores 10 – 12.

32

C. DENSITY – SHEAR STRENGTH RELATION

Hayter (1986) discussed an equation originally derived by Krone (1963) for deriving shear strength, S_u, from density using empirically derived coefficients α and β:

$$S_u = \alpha\rho^\beta$$

Values for α and β must be calculated for each separate sediment type, after which the shear strength can simply be calculated using the coefficients. The scatter diagram between shear strength and density (Fig. 17) doesn't show such an exponential relationship. However, it does indicate that the higher the density, the higher the shear strength.

Shear Strength Vs. Density

Figure 17. Shear Strength Vs. Density analyzed on June 1, 2000.

THIS PAGE INTENTIONALLY LEFT BLANK

V. REAL/MISO DATA ANALYSIS

A. GENERAL INFORMATION OF REAL/MISO

The Monterey Inner Shelf Observatory (MISO) is a component of the Rapid Environmental Assessment Laboratory (REAL) being developed by the oceanography and meteorology departments at the Naval Postgraduate School. REAL encompasses a range of littoral oceanographic observation and modeling programs focused on littoral and coastal oceanography. MISO, designed and implemented by Research Associate Professor Tim Stanton, has a long term cabled instrument frame deployed at the southern end of Monterey Bay in 12m of water, about 600m from the shoreline, with support instruments on the sand dunes inshore from the underwater frame. The instruments on the 12m frame are designed to study the interaction of winds, waves and the sediment bed in the inner continental shelf, just offshore from the surf zone. Observations of the surf zone and breaking waves are made from an automated digital camera located on the sand dune overlooking the underwater frame. By using a high bandwidth multifiber optic and power cable connected to a shore terminus, long term measurements of these important coastal processes can be made for use in research programs and teaching by faculty of the Oceanography Department at the Naval Postgraduate School and shared with other users. Hourly summaries of the data sets are available through the main MISO web site.

An offshore directional wave buoy deployed in January 2000 by Associate Professor Tom Herbers provides hourly updated directional wave spectra and wave height / direction time series.

PHASE 1 R.E.A.L. IMPLEMENTATION

Fig. 18   Phase 1 R.E.A.L Implementation

B. REAL – TIME WAVE DATA

Analysis of wave height data provided by the MISO experiment shows a significant wave motion of approximately 0.5 meters (Figure 19).   Oscillation of wave heights significantly affects water depth and subsequently terminal velocity of the mine upon impact. This is especially significant when running the model in shallow depths.

Although not a parameter considered in the IB model, wave action has a direct effect on water depth and, therefore, on velocity of the mine as it reaches the sediment interface (Taber 1999). This effect only becomes significant when the ratio of water depth to wave height is high, and only at very low release altitudes.

Figure 19. *Hsig Vs. Yearday during the period of the experiment.*

THIS PAGE INTENTIONALLY LEFT BLANK

VI. MINE IMPACT BURIAL

A. HYDRODYNAMIC PROCESSES

IMPACT25 tries to estimate the characteristics of the water column by using fluid drag approximations in its calculations. The essential elements of the mine impact burial model translate into the science and engineering of hydrodynamic process of a falling object and of sediment transport. The current model is only based on the momentum balance of the falling mine,

$$\int \frac{d\mathbf{V}}{dt} dm = \mathbf{F}_{w,a} + \mathbf{F}_b + \mathbf{F}_d$$

where $\mathbf{V}$ is the velocity of the mine, $\mathbf{F}_{w,a}$ is the force due to the air weight of the mine, $\mathbf{F}_b$ is buoyancy force and $\mathbf{F}_d$ is drag force.

Buoyancy force is the upward force exerted upon a mine in the gravitational field by virtue of the density difference between the mine and that of the surrounding fluid. We use the Cartesian coordinate system (x, y, z) with the z-axis in the vertical direction, and use the unit vector $\mathbf{k}$ along the z-axis (pointing downward). The buoyancy force is then computed using the density value for air or water, ρ:

$$\mathbf{F}_b \quad = \quad -\rho\, g\, C\, \mathbf{k}$$

A cylindrical mine penetrating into water passes through two distinct regimes. The first regime is the cavity regime. As the mine pushes into the air-water interface, it creates a cavity that consists of a combination of air and water particles. The ratio of air to water in the cavity decreases until the fluid properties become that of water only, at which time the mine is in the fully wetted regime. A temporal variation of the mine's vertical position can be calculated (Taber 1999; Chu et al. 2000).

When the vertical distance of the mine traveling in the water equals the water depth, the mine velocity is called the bottom impact velocity, which is the initial condition for determining the mine burial depth in the sediment.

Penetration of the cylindrical mine into the bottom sediment depends primarily on the attitude and velocity of the mine upon impact, as well as the sediment properties of density and shear strength. Initial impact of the cylindrical mine into the sediment creates a cavity in which the fluid properties of water and sediment are interacting. The kinematic viscosity of the sediment, Λ_s, is not a pure constant, but rather is equal to the water viscosity, Λ_w, plus that resulting from the shear stress of the sediment:

$$\Lambda_s \quad = \quad \Lambda_w + S_u / (\Delta_s \, dV/dz)$$

where Δ_s is the density of the sediment and S_u is the shear strength.

B. MINE BURIAL DYNAMICS

The vertical momentum balance of a mine in the sediment phase is given by:

$$M_r \, dV/dt = F_{w,a} + F_b + F_d + F_c + F_s$$

where F_b is the buoyancy force in the sediment, F_c is the compressive force, and F_S is the shear force. F_c and F_s are additional forces (different from air and water phases) exerted on the mine by the sediment. They are proportional to shear strength of the sediment and the projected area of the mine. If the mine is a right circular cylinder, the compressive force is twice the shear force:

$$F_c = 2 \, F_s$$
$$F_s = S_u \, A \tag{21}$$

The mine burial depth is predicted by integrating (20) with respect to time until the mine velocity becomes zero. Accurate values for sediment properties are essential to

the accuracy of this process. Shear strength and density have a strong impact on the computation of all forces as well as buoyancy weight and added mass.

THIS PAGE INTENTIONALLY LEFT BLANK

VII. MODEL DATA COMPARISON

A. MODEL DESCRIPTION

Arnone and Bowen developed the impact burial model in 1980. In its original form, it modeled the two-dimensional free-fall history of a right cylinder falling through three phases (air, water, sediment) and predicted the final depth of burial in the sediment. While the concept was accurate, there were a number of problems with the initial model such as a failure to accurately predict terminal velocity in the water column, burial depth in very soft and hard sediments, and unrealistic predictions under some environmental conditions. Recognizing these problems, Satkowiak (1987) made a number of modifications to the basic model. These included:

- Correcting the reference flow area used in the drag calculations

- Correcting the calculation of added mass term

- Including a term to calculate the drag due to the front nose of the cylinder

- Allowing for non-blunt noses of mines

- Including an option to input water temperature

- Including the retarding forces in the sediment due to it's semi-solid nature

- Redefining the method of determining the viscosity and density of the water/sediment mixture during the sediment/cavity regime.

While substantially improving the predictive capability of the model, further improvements were implemented by Hurst. These changes provided new methods for deriving the forces acting on the mine as it passes through the air-water interface and sediment.

B. MODEL DATA COMPARISON

After running the model for each gravity core regime and location, results were averaged and compared with measured data. A chart of the results is found in Figure 20.

Penetration Depth Vs. Drop Number

Figure 20. Measured versus Impact Burial Model output for May 23, 2000.

As evident, the model over predicts actual burial depth by an order of magnitude on average. (See model output Appendix II) Since the gravity cores were taken approximately two to three meters from the impact location, several were taken for each drop. This allowed an average to be calculated in order to yield more accurate results. The model is extremely user-friendly and allows the ability to input the mine dimensions as long as it is a standard cylinder or tapered mine. User input parameters for the environment are in Table 2.

Input Parameters	
Mass of the mine in air	Mass of the mine in water
Mine length	Mine diameter
Mine maximum diameter	Center of mass of the mine
Altitude when released	Angle when released
Initial rotation rate	Water depth
Water temperature	Sediment Density
Sediment shear strength	

Table 2. IMPACT 25 Model Input Parameters

THIS PAGE INTENTIONALLY LEFT BLANK

VIII. CONCLUSIONS

During the Monterey Bay Mine Impact Burial Experiment, the simulated mines were dropped seventeen times. After each drop, the professional divers measured the water temperature, the mine burial depth and took the gravity cores. Core transportation to the United States Geological Society (USGS) occurred immediately upon return to port. Sediment density and sediment shear strength were analyzed from these cores. This experiment provided a synchronous data set on simulated mine burial and ocean environment. This data set to verify the IMPACT25 model found that the model consistently over-predicted the mine impact burial at least an order of magnitude.

Parameters inputted into the IMPACT25 model can be divided among three categories: (1) Oceanographic, which includes water temperature and depth. (2) Physical, which includes release medium, initial velocity, and orientation. (3) Sediment, which includes sediment density and shear strength at varying levels.

It is not believed that there is a problem in how the model interprets the sediment data. Actually, the model is very robust in its ability to allow the user to input multiple sediment layers with varying shear strengths at an impact area. In addition, although not realistic in a real world environment, sediment data was obtained simultaneously with the drops. A major characteristic of ocean sedimentation is that the layers closest to the surface change frequently due to the dynamic conditions at the water-sediment interface. Should the model be applied with dated sediment data, results could be questioned due to the significant change that occurs in sediment in relatively short periods of time.

The physical parameters are the most stable factors in the model. Gravitational acceleration is a constant, and velocity can be readily ascertained through calculations or direct measurement. There is a forewarned problem with specification of inertial spin by the mine when it impacts the air-sea interface. This is not an issue as long as the mine is dropped at a fixed orientation, which was the case during the experiment. The code will certainly not correctly calculate the amount of spin or change in orientation experienced by a mine of varying geometry as it strikes the air-sea interface should it be dropped by an airborne platform.

It is the model's lack of sensitivity to hydrodynamic effects in the water column that provides the greatest error. Any water column in a region exposed to the open ocean such as Monterey Bay will be subject to variances in wave height caused by wind speed and direction. In addition, there will be variances in the momentum flux felt by the column due to current shear in all directions. These effects can cause turbulence in the column that will impede the smooth trajectory of the mine as it travels from the surface to the bottom. Digital video taken during the experiment illustrated the oscillations of the barrel as it traveled through the water column. These oscillations caused by turbulence and flow dynamics of the barrel act as a frictional force in the water and slow its velocity. Although water density is taken into account by the code, in assuming the water column is a uniformly dense and still medium, vertical velocity is overestimated. This overestimated downward vertical velocity can affect the codes calculation of impact force and hence, penetration depth.

The essential elements of the mine impact burial model translate into the science and engineering of hydrodynamic processes for a falling object and of sediment transport.

Any solid object falling through fluid (air and water) should obey two physical principles: (a) momentum balance,

$$\int \frac{d\mathbf{V}}{dt} dm = \mathbf{F}_{w,a} + \mathbf{F}_b + \mathbf{F}_d$$

and (b) moment balance,

$$\int \left[\mathbf{r} \times \left(\frac{d\mathbf{V}}{dt} \right) \right] dm = \mathbf{M}_{w,a} + \mathbf{M}_b + \mathbf{M}_d$$

where $\mathbf{V}$ is the velocity of the mine, and ($\mathbf{F}_{w,a}$, $\mathbf{F}_b$, $\mathbf{F}_d$) are external forces and ($\mathbf{M}_{w,a}$, $\mathbf{M}_b$, $\mathbf{M}_d$) are external moments. The current IMPACT25 model only considers the momentum balance of the mine and disregards the moment balance of the mine. Such an incomplete hydrodynamics in the model leads to unrealistic prediction of the mine falling in the water (no helicoidal motion). If considering momentum and moment balance, the falling object should have a helicoidal motion. Without the helicoidal motion, the IMPACT25 may over-predict the impact burial depth.

Possibilities for error exist in the implementation of the experiment. It was assumed that the barrel was of uniform density because it was filled completely with sand from the beach. This sand was partially wet and contained small amounts of debris which could minutely affect the uniformity of the mine's density and therefore affect oscillation rate. The divers taking the measurements were using meter sticks, and the degree of precision could be called into question. However, errors would most likely not be a full order of magnitude. Most measurements were made on the order of a few centimeters and the code predicted most penetration depths in excess of 10 centimeters.

In conclusion, use of the IMPACT25 prediction model should be approached with caution. Lack of sensitivity to the hydrodynamic effects in the water column cause the code to predict higher downward vertical velocities and therefore a greater impact force

than reality.   Since the sensitivity of a mine can be directly attributed to the amount

exposed, this error can have dire consequences for the operator in the field.

APPENDIX A

Intact Shear Strength

$$Cur = 9.81 \times K \times Wcone / P^2$$

Core number M100mb
Site location Monterey Bay
Date Thursday, June 1st
Technicians Tim, Priscilla

Cone	K
10 and 60 g	0.30
100 and 400 g	1.00

Depth (cm)	W cone (g)	P1	P2	P3	P4	P5	P average	Cur (kPa)
0	100	9	9	11	8.5	9	8.30	14.24
2	100	6	6.5	8	7.5	6	7.20	18.92
4.5	100	7	7	8	6	6	7.00	20.02
6.5	100	7.5	9	7	6	9	7.50	17.44
8.5	100	9	7.5	6.5	7	6	7.00	20.02
10.5	100	5	6	3.5	5	7	5.30	34.92
14.5	100	6	7.5	6.5	5.5	6	6.30	24.72
18.5	100	8	7	6.5	7	8	7.30	18.41
0	100	14	11	11.5	10.5	8.5	11.10	7.96
2	100	7	7.5	9	9.5	7	8.00	15.33
4	100	7	8	10	8	9	8.40	13.90
6	100	9.5	7.5	9	8.5	7	8.30	14.24
8	100	8	8	7.5	9	7	7.90	15.72
10	100	8	6	7	9	8.5	7.70	16.55
14	100	5	9	8.5	6	8	7.30	18.41
18	100	5	6	5.5	8	6	6.10	26.36
0	100	10.5	10	8	8	8	8.90	12.38
2	100	8	8	9	8	8	8.20	14.59
4	100	9	7	8	7	9.5	8.10	14.95
6	100	7	8	5.5	7	7	6.90	20.60
8	400	11.5	12	10.5	10	13	11.40	30.19
10	400	11	12	11.5	11	12	11.50	29.67
14	400	13	10.5	12	11.5	12	11.80	28.18
0	100	12	10	9	8.5	9.5	9.80	10.21
2	100	9	7	6	7.5	8.5	7.60	16.98
4	100	8	6	7	9	6	7.20	18.92
6	100	8	7.5	8	8	7.5	7.80	16.12
8	100	8	8	6.5	7	7.5	7.40	17.91
10	100	8	8	7	5	6.5	6.90	20.60
14	100	11	9	7	10	7	8.80	12.67
18	100	7.5	7	7.5	8	6.5	7.30	18.41
22	100	9	8	7.5	10	7	8.30	14.24
0	60	10	10	8	8	10	9.20	2.09
2	100	6	6.5	6.5	7	7	6.60	22.52
4	100	6	5	5	7	6	5.80	29.16
6	100	7.5	6	5	5	6.5	6.00	27.25
8	100	6	5	6	5	6	5.60	31.28
10	100	6	8	8	10	5	7.40	17.91
0	60	11	12	14	13.5	13.5	12.80	1.08
2	100	7	8	10	10	9	8.80	12.67
4	100	8	8	7	8	8	7.80	16.12
6	100	9	8.5	6	8	6.5	7.60	16.98
8	100	7	6	8	7.5	6.5	7.00	20.02
10	100	7	6	6.5	5.5	5.5	6.10	26.36
14	100	7.5	5.5	6	8	7	6.80	21.22
18	100	9	8.5	7.5	8	7.5	8.10	14.95
0	60	8	9	10	12	9	9.60	1.92
2	100	8	7.5	6	6.5	7	7.00	20.02
4	100	6.5	6.5	6	8	6	6.60	22.52
6	100	5	5	6	7	5	5.60	31.28
8	100	7	5	5	7	5	5.80	29.16
10	100	6	6	5	5	7	5.80	29.16
14	100	5	6	5	5	6	5.40	33.64
18	100	5	7	6	8	7.5	6.70	21.85

Intact Shear Strength

$$\text{Cur} = 9.81 \times K \times \text{Wcone} / P^2$$

Core number M100mb
Site location Monterey Bay
Date Thursday, June 1st
Technicians Tim, Priscilla

Cone	K
10 and 60 g	0.30
100 and 400 g	1.00

Depth (cm)	W cone (g)	P1	P2	P3	P4	P5	P average	Cur (kPa)
0	60	9	9.5	10.5	10	9.5	9.70	1.88
3	100	7	6	8	7.5	8	7.70	16.55
3	100	7	7	7.5	7.5	5	6.80	21.22
5	100	8	8.5	5	8.5	7	7.60	16.98
8	100	7	6	6	6	8	7.20	18.92
10	100	8.5	6	10	7	7.5	8.40	13.90
14	100	6.5	6.5	7	9	5.5	6.90	20.60
18	100	8	5	6	7.5	6	6.50	23.22
0	60	10.5	8.5	9.5	9.5	11.5	9.90	1.80
2	100	6	7	6	6	6.5	6.30	24.72
4	100	5.5	5	5	5	7	5.50	32.43
6	100	6.5	5.5	6.5	8	5.5	6.40	23.95
8	100	7	5	5	6	5	5.60	31.28
10	100	6	5	6	6	6	5.80	29.16
16	100	8	6	6.5	8	6	6.90	20.60
0	100	14	11	12	9	6.5	10.50	8.90
2	100	6.5	8	8.5	9.5	6.5	7.80	16.12
4	100	8.5	9.5	7	8	7	8.00	15.33
6	100	9.5	6.5	5	8	9	7.60	16.98
8	100	9	9.5	6.5	7.5	8	8.10	14.95
10	100	10	9.5	9	7	9	8.90	12.38
14	100	6	7.5	8	8	9.5	7.80	16.12
18	100	11	8	8.5	10	5	8.50	13.58
22	100	8	8	8	9	7	8.00	15.33
0	100	14	11	11.5	10.5	8.5	11.10	7.96
2	100	7	7.5	9	9.5	7	8.00	15.33
4	100	7	8	10	8	9	8.40	13.90
6	100	9.5	7.5	9	8.5	7	8.30	14.24
8	100	8	8	7.5	9	7	7.90	15.72
10	100	8	6	7	9	8.5	7.70	16.55
14	100	5	9	8.5	6	8	7.30	18.41
18	100	5	6	5.5	8	6	6.10	26.36

Water Content

Core number M100mb
Site location Monterey Bay
Date Thursday June 1st
Technicians Tim , Priscilla

Depth (cm)	Tare Weight (g)	Humide Weight (g)	Dry Weight (g)	H2O Content (w%)	w% corrected	Density (kg/m3)
1	6.30	22.80	19.10	28.91	30.03	1898.43
3.25	4.39	21.70	17.95	27.65	28.72	1915.96
5.5	4.40	21.57	17.95	26.72	27.74	1929.57
7.5	4.27	20.14	16.82	26.45	27.47	1933.43
9.5	4.33	21.65	18.15	25.33	26.29	1950.45
12.5	4.38	22.55	18.65	27.33	28.38	1920.63
16.5	4.48	23.34	18.65	33.10	34.43	1844.21
19.75	4.27	30.06	23.49	34.18	35.57	1831.21
1	4.46	26.38	21.21	30.87	32.09	1872.26
5	4.49	22.70	18.35	31.39	32.63	1865.57
5	4.43	20.81	16.78	32.63	33.94	1849.93
7	4.46	19.22	15.65	31.90	33.18	1859.00
5	4.41	22.61	18.23	31.69	32.96	1861.66
12	4.50	25.02	20.57	27.69	28.76	1915.44
16	6.38	33.48	27.58	27.83	28.91	1913.47
21	4.50	28.37	23.19	27.72	28.79	1915.10
1	4.48	22.27	18.33	28.45	29.55	1904.78
3	4.34	21.12	17.49	27.60	28.67	1916.68
5	4.42	20.50	17.12	26.61	27.63	1931.06
7	4.52	18.75	15.18	33.49	34.84	1839.47
5	4.37	17.54	14.74	27.00	28.04	1925.40
12	4.37	24.07	19.60	29.35	30.50	1892.37
16.5	4.48	18.92	15.60	29.86	31.03	1885.56
1	4.39	17.49	14.73	26.69	27.72	1929.91
3	4.40	15.83	13.55	24.92	25.86	1956.75
5	4.33	23.75	19.37	29.12	30.26	1895.47
7	4.44	20.49	16.46	33.53	34.88	1839.02
9	4.37	24.45	19.84	29.80	30.97	1886.31
12	4.29	23.61	18.89	32.33	33.62	1853.68
16	4.48	28.69	23.96	24.28	25.19	1966.75
20	4.45	23.60	19.79	24.84	25.77	1958.01
24	4.32	28.25	23.25	26.41	27.42	1934.04
1	6.70	20.43	17.39	28.44	29.54	1904.92
3	6.35	28.36	23.62	27.45	28.50	1918.95
5	4.31	18.07	14.81	31.05	32.28	1869.91
7	6.63	26.80	22.30	28.72	29.84	1901.04
9	4.41	20.52	16.94	28.57	29.68	1903.06
12.5	6.45	23.88	19.96	29.02	30.15	1896.93
1	4.29	26.54	20.86	34.28	35.67	1830.08
3	4.37	24.28	19.67	30.13	31.32	1881.90
5	4.38	26.71	21.92	27.31	28.36	1920.93
7	4.30	27.00	22.33	25.90	26.89	1941.69
9	4.48	24.61	19.91	30.46	31.66	1877.56
12	4.39	26.18	21.69	25.95	26.94	1940.90
16	4.40	24.33	20.00	27.76	28.83	1914.52
19.5	4.31	21.98	17.68	32.16	33.45	1855.76
1	6.32	22.23	18.32	32.58	33.89	1850.52
3	4.46	22.33	18.47	27.55	28.61	1917.44
5	4.50	23.63	19.85	24.63	25.55	1961.32
7	4.39	24.90	20.54	27.00	28.03	1925.45
9	6.19	26.07	21.93	26.30	27.31	1935.68
12	4.42	22.96	19.12	26.12	27.12	1938.37
16	4.41	23.35	19.23	27.80	28.88	1913.89
21	4.30	25.40	20.12	33.38	34.72	1840.85

Water Content

Core number M100mb
Site location Monterey Bay
Date Thursday June 1st
Technicians Tim , Priscilla

Depth (cm)	Tare Weight (g)	Humide Weight (g)	Dry Weight (g)	H2O Content (w%)	w% corrected	Density (kg/m3)
1	4.32	20.53	16.48	33.31	34.65	1841.69
3	4.34	26.24	21.55	27.25	28.30	1921.76
3	4.34	20.40	17.06	26.26	27.26	1936.35
7	6.31	29.48	24.71	25.92	26.91	1941.35
3	4.44	19.24	16.74	20.33	21.06	2033.83
12	4.36	28.42	24.05	22.19	23.01	2001.04
16	4.50	20.85	17.35	27.24	28.29	1921.96
19.5	4.50	27.73	22.84	26.66	27.68	1930.34
1	4.42	22.95	18.49	31.70	32.96	1861.59
3	4.27	24.77	19.91	31.07	32.31	1869.57
5	4.27	19.75	16.03	31.63	32.89	1862.42
7	4.50	26.00	21.24	28.43	29.54	1904.96
3	6.36	26.46	21.78	30.35	31.55	1879.00
13	4.40	22.90	18.57	30.56	31.77	1876.28
16	6.42	31.67	26.06	28.56	29.68	1903.16
1	4.37	21.40	18.04	24.58	25.50	1962.04
3	4.45	23.39	19.17	28.67	29.78	1901.71
5	4.45	20.16	16.96	25.58	26.55	1946.57
7	4.46	22.20	18.48	26.53	27.55	1932.25
9	4.37	22.41	18.92	23.99	24.88	1971.46
12	4.33	25.47	22.18	18.43	19.09	2069.28
16	4.38	26.77	22.48	23.70	24.59	1976.04
20	4.45	24.86	19.85	32.53	33.84	1851.15
23	4.52	20.27	16.65	29.84	31.02	1885.73
1	4.38	29.57	24.09	27.80	28.88	1913.85
3	4.42	19.36	16.65	22.16	22.98	2001.64
5	6.47	27.98	23.29	27.88	28.96	1912.71
7	4.30	25.00	20.46	28.09	29.18	1909.74
9	4.42	23.95	19.76	27.31	28.37	1920.85
12	6.26	26.79	22.10	29.61	30.77	1888.88
16	4.45	24.73	20.15	29.17	30.31	1894.79
20.5	4.48	29.63	24.19	27.60	28.67	1916.75

APPENDIX B

```
**************************************************************
******         NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #1 Core #1       Date,Time: 06-21-2000     11:27:53
Speed mode: Rigorous
--------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                       (kg)                    294.835
Apparent mass in water     (kg)                    31.873
Overall length             (m)                     .8763
Maximum diameter           (m)                     .6096
Length of taper on base    (m)                     0
Minimum taper diameter     (m)                     .6096
Distance of CM from centre (m)                     0
External surface area    (sq m)                    2.262
Volume of mine           (cu m)                    0.256


--------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)               0
Horiz vel (rightward pos)                  0
Angle(0 vertical,90 horizontal)            0
Rotation rate(rad/sec cl'wise)             0
Water depth (m):                           11.887
Temperature (deg C):                       12

Sediment characteristics:  CORE1
  Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------      ---------------   ----------------  --------------------
     1            .02              1898.43              14240
     2            .045             1915.96              18920
     3            .065             1929.57              20020
     4            .085             1933.43              17440
     5            .105             1950.45              20020
     6            .145             1920.63              34920
     7            .185             1844.21              24720
     8            5                1844.21              24720
```

WATER PHASE

```
-------------------------------------------------------------------
    Time        Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
    (sec)       (m)          (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
    0.000       0.000        0.000        0.000        0.000        0.000
    0.510       0.108        0.411        0.000        0.000        0.000
    1.010       0.407        0.764        0.000        0.000    .    0.000
    1.510       0.862        1.039        0.000        0.000        0.000
    2.010       1.435        1.235        0.000        0.000        0.000
    2.510       2.088        1.365        0.000        0.000        0.000
    3.010       2.793        1.448        0.000        0.000        0.000
    3.510       3.532        1.499        0.000        0.000        0.000
    4.010       4.290        1.531        0.000        0.000        0.000
    4.500       5.045        1.549        0.000        0.000        0.000
    5.000       5.822        1.560        0.000        0.000        0.000
    5.500       6.604        1.567        0.000        0.000        0.000
    6.000       7.389        1.571        0.000        0.000        0.000
    6.500       8.175        1.573        0.000        0.000        0.000
    7.000       8.962        1.575        0.000        0.000        0.000
    7.500       9.750        1.575        0.000        0.000        0.000
    8.000      10.537        1.576        0.000        0.000        0.000
    8.500      11.325        1.576        0.000        0.000        0.000
    8.860      11.893        1.576        0.000        0.000        0.000
```
Accumulated transverse movement   0.0 m

SEDIMENT PHASE

```
-------------------------------------------------------------------
    Time        Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
    (sec)       (m)          (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
    0.000       0.000        1.576        0.000        0.000        0.000
    0.103       0.096        0.314       -0.004        0.019        0.002
    0.126       0.100        0.019       -0.004        0.020        0.001
```

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.777   metres
Area exposed: 1.780   sq m   (79% of total)
Volume exposed: 0.2267 cu m   (89% of total)

```
*************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997
```

Run name: Drop #1 Core #2   Date,Time: 06-21-2000   11:28:34
Speed mode: Rigorous

Mine characteristics,   55GALDRM

Mass	(kg)		294.835
Apparent mass in water	(kg)		31.873
Overall length	(m)		.8763
Maximum diameter	(m)		.6096
Length of taper on base	(m)		0
Minimum taper diameter	(m)		.6096
Distance of CM from centre	(m)		0
External surface area	(sq m)		2.262
Volume of mine	(cu m)		0.256

RELEASE CONDITIONS

Vert vel (downward positive)		0
Horiz vel (rightward pos)		0
Angle(0 vertical,90 horizontal)		0
Rotation rate(rad/sec cl'wise)		0
Water depth (m):		11.887
Temperature (deg C):		12

Sediment characteristics: CORE2

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1872.26	7960
2	.04	1865.57	15330
3	.06	1849.93	13900
4	.08	1859	14240
5	.1	1862	15720
6	.14	1915	16550
7	.18	1913	18410
8	5	1913	18410

WATER PHASE

```
--------------------------------------------------------------------------
   Time       Depth       Vert       Horiz      Ang        Angle
                          Vel        Vel        Vel
   (sec)      (m)         (m/s)      (m/s)      (rad/s)    (deg)
 --------    --------    --------   --------   --------   -------
   0.000      0.000       0.000      0.000      0.000      0.000
   0.510      0.108       0.411      0.000      0.000      0.000
   1.010      0.407       0.764      0.000      0.000      0.000
   1.510      0.862       1.039      0.000      0.000      0.000
   2.010      1.435       1.235      0.000      0.000      0.000
   2.510      2.088       1.365      0.000      0.000      0.000
   3.010      2.793       1.448      0.000      0.000      0.000
   3.510      3.532       1.499      0.000      0.000      0.000
   4.010      4.290       1.531      0.000      0.000      0.000
   4.500      5.045       1.549      0.000      0.000      0.000
   5.000      5.822       1.560      0.000      0.000      0.000
   5.500      6.604       1.567      0.000      0.000      0.000
   6.000      7.389       1.571      0.000      0.000      0.000
   6.500      8.175       1.573      0.000      0.000      0.000
   7.000      8.962       1.575      0.000      0.000      0.000
   7.500      9.750       1.575      0.000      0.000      0.000
   8.000     10.537       1.576      0.000      0.000      0.000
   8.500     11.325       1.576      0.000      0.000      0.000
   8.860     11.893       1.576      0.000      0.000      0.000
Accumulated transverse movement      0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
   Time       Depth       Vert       Horiz      Ang        Angle
                          Vel        Vel        Vel
   (sec)      (m)         (m/s)      (m/s)      (rad/s)    (deg)
 --------    --------    --------   --------   --------   -------
   0.000      0.000       1.576      0.000      0.000      0.000
   0.103      0.112       0.559     -0.003      0.015      0.001
   0.151      0.126       0.046      0.005     -0.022     -0.001
```

BURIAL RESULT:

Depth of burial: 0.126   metres

Height protruding: 0.751   metres
Area exposed: 1.729   sq m   (76% of total)
Volume exposed: 0.2191 cu m   (86% of total)

```
************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997
```

Run name: Drop #1 Core #3   Date,Time: 06-21-2000   11:29:12
Speed mode: Rigorous

Mine characteristics,   55GALDRM

Mass	(kg)	294.835
Apparent mass in water	(kg)	31.873
Overall length	(m)	.8763
Maximum diameter	(m)	.6096
Length of taper on base	(m)	0
Minimum taper diameter	(m)	.6096
Distance of CM from centre	(m)	0
External surface area	(sq m)	2.262
Volume of mine	(cu m)	0.256

RELEASE CONDITIONS

Vert vel (downward positive)	0
Horiz vel (rightward pos)	0
Angle(0 vertical,90 horizontal)	0
Rotation rate(rad/sec cl'wise)	0
Water depth (m):	11.887
Temperature (deg C):	12

Sediment characteristics: CORE3

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1904.78	12380
2	.04	1917	14590
3	.06	1931	14950
4	.08	1839	20600
5	.1	1925	30190
6	.14	1892	29670
7	.18	1886	28180
8	5	1886	28180

WATER PHASE

```
-------------------------------------------------------------------------------
    Time        Depth        Vert        Horiz       Ang         Angle
                             Vel         Vel         Vel
    (sec)        (m)         (m/s)       (m/s)       (rad/s)     (deg)
   ---------   ---------   ---------   ---------   ---------   -------
    0.000       0.000       0.000       0.000       0.000       0.000
    0.510       0.108       0.411       0.000       0.000       0.000
    1.010       0.407       0.764       0.000       0.000       0.000
    1.510       0.862       1.039       0.000       0.000       0.000
    2.010       1.435       1.235       0.000       0.000       0.000
    2.510       2.088       1.365       0.000       0.000       0.000
    3.010       2.793       1.448       0.000       0.000       0.000
    3.510       3.532       1.499       0.000       0.000       0.000
    4.010       4.290       1.531       0.000       0.000       0.000
    4.500       5.045       1.549       0.000       0.000       0.000
    5.000       5.822       1.560       0.000       0.000       0.000
    5.500       6.604       1.567       0.000       0.000       0.000
    6.000       7.389       1.571       0.000       0.000       0.000
    6.500       8.175       1.573       0.000       0.000       0.000
    7.000       8.962       1.575       0.000       0.000       0.000
    7.500       9.750       1.575       0.000       0.000       0.000
    8.000      10.537       1.576       0.000       0.000       0.000
    8.500      11.325       1.576       0.000       0.000       0.000
    8.860      11.893       1.576       0.000       0.000       0.000
Accumulated transverse movement    0.0 m
```

SEDIMENT PHASE

```
-------------------------------------------------------------------------------
    Time        Depth        Vert        Horiz       Ang         Angle
                             Vel         Vel         Vel
    (sec)        (m)         (m/s)       (m/s)       (rad/s)     (deg)
   ---------   ---------   ---------   ---------   ---------   -------
    0.000       0.000       1.576       0.000       0.000       0.000
    0.102       0.098       0.148       0.003      -0.014      -0.001
    0.107       0.098       0.049       0.003      -0.014      -0.001
```

BURIAL RESULT:

Depth of burial: 0.098   metres

Height protruding: 0.778   metres
Area exposed: 1.782   sq m   (79% of total)
Volume exposed: 0.2270 cu m   (89% of total)

60

```
*******************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #2 Core #1      Date,Time: 06-21-2000      11:30:06
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,      55GALDRM

Mass                       (kg)              294.835
Apparent mass in water     (kg)              31.873
Overall length             (m)               .8763
Maximum diameter           (m)               .6096
Length of taper on base    (m)               0
Minimum taper diameter     (m)               .6096
Distance of CM from centre (m)               0
External surface area      (sq m)            2.262
Volume of mine             (cu m)            0.256


-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE1
```

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1898.43	14240
2	.045	1915.96	18920
3	.065	1929.57	20020
4	.085	1933.43	17440
5	.105	1950.45	20020
6	.145	1920.63	34920
7	.185	1844.21	24720
8	5	1844.21	24720

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.103	0.106	0.350	0.004	-0.011	89.990
0.121	0.109	0.047	-0.003	0.008	89.993

BURIAL RESULT:

Depth of burial: 0.109 metres

Height protruding: 0.500 metres
Area exposed: 1.723 sq m   (76% of total)
Volume exposed: 0.2246 cu m   (88% of total)

```
************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL           ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #2 Core #2      Date,Time: 06-21-2000      11:30:50
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                        (kg)                294.835
Apparent mass in water      (kg)                31.873
Overall length              (m)                 .8763
Maximum diameter            (m)                 .6096
Length of taper on base     (m)                 0
Minimum taper diameter      (m)                 .6096
Distance of CM from centre  (m)                 0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256


-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12


Sediment characteristics:  CORE2
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------      ---------------    ----------------   --------------------
    1            .02              1872.26              7960
    2            .04              1865.57              15330
    3            .06              1849.93              13900
    4            .08              1859                 14240
    5            .1               1862                 15720
    6            .14              1915                 16550
    7            .18              1913                 18410
    8           5                 1913                 18410
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.100	0.117	0.623	0.001	-0.004	89.996
0.145	0.131	0.048	-0.004	0.011	89.993

BURIAL RESULT:

Depth of burial: 0.131 metres

Height protruding: 0.479 metres
Area exposed: 1.656 sq m   (73% of total)
Volume exposed: 0.2155 cu m   (84% of total)

```
************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #2 Core #3        Date,Time: 06-21-2000      11:31:24
Speed mode: Rigorous
----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                       (kg)                  294.835
Apparent mass in water     (kg)                  31.873
Overall length             (m)                   .8763
Maximum diameter           (m)                   .6096
Length of taper on base    (m)                   0
Minimum taper diameter     (m)                   .6096
Distance of CM from centre (m)                   0
External surface area    (sq m)                  2.262
Volume of mine           (cu m)                  0.256


----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE3
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------  --------------------
    1             .02             1904.78            12380
    2             .04             1917               14590
    3             .06             1931               14950
    4             .08             1839               20600
    5             .1              1925               30190
    6             .14             1892               29670
    7             .18             1886               28180
    8             5               1886               28180
```

WATER PHASE

```
---------------------------------------------------------------------
   Time        Depth        Vert         Horiz        Ang          Angle
                            Vel          Vel          Vel
   (sec)       (m)          (m/s)        (m/s)        (rad/s)      (deg)
   --------    --------     --------     --------     --------     -------
   0.000       0.000        0.000        0.000        0.000        90.000
   0.510       0.089        0.335       -0.000        0.000        90.000
   1.010       0.330        0.617       -0.000        0.000        90.000
   1.510       0.709        0.893       -0.000        0.000        90.000
   2.010       1.216        1.117       -0.000        0.000        90.000
   2.510       1.818        1.278       -0.000        0.000        90.000
   3.010       2.486        1.386       -0.000        0.000        90.000
   3.510       3.198        1.455       -0.000        0.000        90.000
   4.010       3.938        1.498       -0.000        0.000        90.000
   4.500       4.679        1.524       -0.000        0.000        90.000
   5.000       5.446        1.540       -0.000        0.000        90.000
   5.500       6.219        1.550       -0.000        0.000        90.000
   6.000       6.995        1.556       -0.000        0.000        90.000
   6.500       7.774        1.559       -0.000        0.000        90.000
   7.000       8.555        1.561       -0.000        0.000        90.000
   7.500       9.336        1.563       -0.000        0.000        90.000
   8.000      10.117        1.563       -0.000        0.000        90.000
   8.500      10.899        1.564       -0.000        0.000        90.000
   9.000      11.681        1.564       -0.000        0.000        90.000
   9.500      12.463        1.564       -0.000        0.000        90.000
   9.530      12.510        1.564       -0.000        0.000        90.000
Accumulated transverse movement   -0.0 m
```

SEDIMENT PHASE

```
---------------------------------------------------------------------
   Time        Depth        Vert         Horiz        Ang          Angle
                            Vel          Vel          Vel
   (sec)       (m)          (m/s)        (m/s)        (rad/s)      (deg)
   --------    --------     --------     --------     --------     -------
   0.000       0.000        1.564       -0.000        0.000        90.000
   0.101       0.108        0.341       -0.003        0.008        89.993
   0.117       0.111        0.044       -0.002        0.006        89.995
```

BURIAL RESULT:

Depth of burial: 0.111   metres

Height protruding: 0.499   metres
Area exposed: 1.718   sq m   (76% of total)
Volume exposed: 0.2239 cu m   (88% of total)

66

```
********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #3 Core #1        Date,Time: 06-21-2000      11:32:15
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                       (kg)            294.835
Apparent mass in water     (kg)            31.873
Overall length             (m)             .8763
Maximum diameter           (m)             .6096
Length of taper on base    (m)             0
Minimum taper diameter     (m)             .6096
Distance of CM from centre (m)             0
External surface area    (sq m)            2.262
Volume of mine           (cu m)            0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE1
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ---------------   --------------------
    1            .02              1898.43              14240
    2            .045             1915.96              18920
    3            .065             1929.57              20020
    4            .085             1933.43              17440
    5            .105             1950.45              20020
    6            .145             1920.63              34920
    7            .185             1844.21              24720
    8           5                1844.21              24720
```

67

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.103	0.106	0.350	0.004	-0.011	89.990
0.121	0.109	0.047	-0.003	0.008	89.993

BURIAL RESULT:

Depth of burial: 0.109   metres

Height protruding: 0.500   metres
Area exposed: 1.723   sq m   (76% of total)
Volume exposed: 0.2246 cu m   (88% of total)

```
***********************************************************************
******      NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #3 Core #2        Date,Time: 06-21-2000      11:32:49
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                      (kg)              294.835
Apparent mass in water    (kg)               31.873
Overall length             (m)               .8763
Maximum diameter           (m)               .6096
Length of taper on base    (m)              0
Minimum taper diameter     (m)               .6096
Distance of CM from centre (m)              0
External surface area    (sq m)              2.262
Volume of mine           (cu m)             0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE2
  Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------     ---------------   ---------------   --------------------
     1           .02              1872.26              7960
     2           .04              1865.57             15330
     3           .06              1849.93             13900
     4           .08              1859                14240
     5           .1               1862                15720
     6           .14              1915                16550
     7           .18              1913                18410
     8          5                 1913                18410
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.100	0.117	0.623	-0.002	0.005	89.997
0.145	0.131	0.048	0.000	-0.000	89.990

BURIAL RESULT:

Depth of burial: 0.131 metres

Height protruding: 0.479 metres
Area exposed: 1.656 sq m   (73% of total)
Volume exposed: 0.2155 cu m   (84% of total)

```
*************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL           ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #3 Core #3        Date,Time: 06-21-2000      11:33:18
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,         55GALDRM

Mass                        (kg)                   294.835
Apparent mass in water      (kg)                   31.873
Overall length              (m)                    .8763
Maximum diameter            (m)                    .6096
Length of taper on base     (m)                    0
Minimum taper diameter      (m)                    .6096
Distance of CM from centre  (m)                    0
External surface area    (sq m)                    2.262
Volume of mine           (cu m)                    0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12

Sediment characteristics:  CORE3
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------      ---------------    ----------------   --------------------
    1            .02               1904.78              12380
    2            .04               1917                 14590
    3            .06               1931                 14950
    4            .08               1839                 20600
    5            .1                1925                 30190
    6            .14               1892                 29670
    7            .18               1886                 28180
    8            5                 1886                 28180
```

WATER PHASE

```
----------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang       Angle
                             Vel          Vel         Vel
   (sec)         (m)        (m/s)        (m/s)      (rad/s)     (deg)
 --------     ---------    ---------    ---------   ---------   -------
   0.000        0.000        0.000        0.000       0.000     90.000
   0.510        0.089        0.335       -0.000       0.000     90.000
   1.010        0.330        0.617       -0.000       0.000     90.000
   1.510        0.709        0.893       -0.000       0.000     90.000
   2.010        1.216        1.117       -0.000       0.000     90.000
   2.510        1.818        1.278       -0.000       0.000     90.000
   3.010        2.486        1.386       -0.000       0.000     90.000
   3.510        3.198        1.455       -0.000       0.000     90.000
   4.010        3.938        1.498       -0.000       0.000     90.000
   4.500        4.679        1.524       -0.000       0.000     90.000
   5.000        5.446        1.540       -0.000       0.000     90.000
   5.500        6.219        1.550       -0.000       0.000     90.000
   6.000        6.995        1.556       -0.000       0.000     90.000
   6.500        7.774        1.559       -0.000       0.000     90.000
   7.000        8.555        1.561       -0.000       0.000     90.000
   7.500        9.336        1.563       -0.000       0.000     90.000
   8.000       10.117        1.563       -0.000       0.000     90.000
   8.500       10.899        1.564       -0.000       0.000     90.000
   9.000       11.681        1.564       -0.000       0.000     90.000
   9.140       11.900        1.564       -0.000       0.000     90.000
Accumulated transverse movement   -0.0 m
```

SEDIMENT PHASE

```
----------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang       Angle
                             Vel          Vel         Vel
   (sec)         (m)        (m/s)        (m/s)      (rad/s)     (deg)
 --------     ---------    ---------    ---------   ---------   -------
   0.000        0.000        1.564       -0.000       0.000     90.000
   0.101        0.108        0.341       -0.003       0.008     89.993
   0.117        0.111        0.044       -0.002       0.006     89.995
```

BURIAL RESULT:

Depth of burial: 0.111 metres

Height protruding: 0.499 metres
Area exposed: 1.718 sq m   (76% of total)
Volume exposed: 0.2239 cu m   (88% of total)

Run name: Drop #4 Core #1   Date,Time: 06-21-2000   11:34:02
Speed mode: Rigorous

Mine characteristics,   55GALDRM

Mass	(kg)	294.835
Apparent mass in water	(kg)	31.873
Overall length	(m)	.8763
Maximum diameter	(m)	.6096
Length of taper on base	(m)	0
Minimum taper diameter	(m)	.6096
Distance of CM from centre	(m)	0
External surface area	(sq m)	2.262
Volume of mine	(cu m)	0.256

RELEASE CONDITIONS

Vert vel (downward positive)	0
Horiz vel (rightward pos)	0
Angle(0 vertical,90 horizontal)	90
Rotation rate(rad/sec cl'wise)	0
Water depth (m):	11.887
Temperature (deg C):	12

Sediment characteristics: CORE1

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1898.43	14240
2	.045	1915.96	18920
3	.065	1929.57	20020
4	.085	1933.43	17440
5	.105	1950.45	20020
6	.145	1920.63	34920
7	.185	1844.21	24720
8	5	1844.21	24720

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.103	0.106	0.350	0.004	-0.011	89.990
0.121	0.109	0.047	-0.003	0.008	89.993

BURIAL RESULT:

Depth of burial: 0.109 metres

Height protruding: 0.500 metres
Area exposed: 1.723 sq m   (76% of total)
Volume exposed: 0.2246 cu m   (88% of total)

```
**************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #4 Core #2       Date,Time: 06-21-2000      11:34:31
Speed mode: Rigorous
--------------------------------------------------------------------
Mine characteristics,      55GALDRM

Mass                       (kg)                  294.835
Apparent mass in water     (kg)                  31.873
Overall length             (m)                   .8763
Maximum diameter           (m)                   .6096
Length of taper on base    (m)                   0
Minimum taper diameter     (m)                   .6096
Distance of CM from centre (m)                   0
External surface area    (sq m)                  2.262
Volume of mine           (cu m)                  0.256


--------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12


Sediment characteristics:  CORE2
 Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     --------------    ---------------   --------------------
    1          .02             1872.26            7960
    2          .04             1865.57            15330
    3          .06             1849.93            13900
    4          .08             1859               14240
    5          .1              1862               15720
    6          .14             1915               16550
    7          .18             1913               18410
    8          5               1913               18410
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

_____

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.100	0.117	0.623	-0.002	0.005	89.997
0.145	0.131	0.048	0.000	-0.000	89.990

_____

BURIAL RESULT:

Depth of burial: 0.131 metres

Height protruding: 0.479 metres
Area exposed: 1.656 sq m   (73% of total)
Volume exposed: 0.2155 cu m   (84% of total)

```
***********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #4 Core #3        Date,Time: 06-21-2000      11:35:03
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area     (sq m)              2.262
Volume of mine            (cu m)              0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12


Sediment characteristics:  CORE3
```

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1904.78	12380
2	.04	1917	14590
3	.06	1931	14950
4	.08	1839	20600
5	.1	1925	30190
6	.14	1892	29670
7	.18	1886	28180
8	5	1886	28180

WATER PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang         Angle
                             Vel         Vel          Vel
   (sec)         (m)        (m/s)       (m/s)       (rad/s)       (deg)
  --------     --------    --------    --------    --------     -------
   0.000        0.000       0.000       0.000       0.000       90.000
   0.510        0.089       0.335      -0.000       0.000       90.000
   1.010        0.330       0.617      -0.000       0.000       90.000
   1.510        0.709       0.893      -0.000       0.000       90.000
   2.010        1.216       1.117      -0.000       0.000       90.000
   2.510        1.818       1.278      -0.000       0.000       90.000
   3.010        2.486       1.386      -0.000       0.000       90.000
   3.510        3.198       1.455      -0.000       0.000       90.000
   4.010        3.938       1.498      -0.000       0.000       90.000
   4.500        4.679       1.524      -0.000       0.000       90.000
   5.000        5.446       1.540      -0.000       0.000       90.000
   5.500        6.219       1.550      -0.000       0.000       90.000
   6.000        6.995       1.556      -0.000       0.000       90.000
   6.500        7.774       1.559      -0.000       0.000       90.000
   7.000        8.555       1.561      -0.000       0.000       90.000
   7.500        9.336       1.563      -0.000       0.000       90.000
   8.000       10.117       1.563      -0.000       0.000       90.000
   8.500       10.899       1.564      -0.000       0.000       90.000
   9.000       11.681       1.564      -0.000       0.000       90.000
   9.140       11.900       1.564      -0.000       0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang         Angle
                             Vel         Vel          Vel
   (sec)         (m)        (m/s)       (m/s)       (rad/s)       (deg)
  --------     --------    --------    --------    --------     -------
   0.000        0.000       1.564      -0.000       0.000       90.000
   0.101        0.108       0.341      -0.003       0.008       89.993
   0.117        0.111       0.044      -0.002       0.006       89.995
```

BURIAL RESULT:

Depth of burial: 0.111 metres

Height protruding: 0.499 metres
Area exposed: 1.718 sq m   (76% of total)
Volume exposed: 0.2239 cu m   (88% of total)

78

```
**************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #5 Core #1       Date,Time: 06-21-2000      11:35:56
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                      (kg)                  294.835
Apparent mass in water    (kg)                  31.873
Overall length             (m)                  .8763
Maximum diameter           (m)                  .6096
Length of taper on base    (m)                  0
Minimum taper diameter     (m)                  .6096
Distance of CM from centre (m)                  0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12


Sediment characteristics:  CORE1
  Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
  ------      ----------------   ----------------   --------------------
     1             .02              1898.43               14240
     2             .045             1915.96               18920
     3             .065             1929.57               20020
     4             .085             1933.43               17440
     5             .105             1950.45               20020
     6             .145             1920.63               34920
     7             .185             1844.21               24720
     8            5                 1844.21               24720
```

WATER PHASE

```
----------------------------------------------------------------------
   Time         Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
   (sec)        (m)          (m/s)        (m/s)        (rad/s)      (deg)
 --------     --------     --------     --------     --------     -------
   0.000        0.000        0.000        0.000        0.000       90.000
   0.510        0.089        0.335       -0.000        0.000       90.000
   1.010        0.330        0.617       -0.000        0.000       90.000
   1.510        0.709        0.893       -0.000        0.000       90.000
   2.010        1.216        1.117       -0.000        0.000       90.000
   2.510        1.818        1.278       -0.000        0.000       90.000
   3.010        2.486        1.386       -0.000        0.000       90.000
   3.510        3.198        1.455       -0.000        0.000       90.000
   4.010        3.938        1.498       -0.000        0.000       90.000
   4.500        4.679        1.524       -0.000        0.000       90.000
   5.000        5.446        1.540       -0.000        0.000       90.000
   5.500        6.219        1.550       -0.000        0.000       90.000
   6.000        6.995        1.556       -0.000        0.000       90.000
   6.500        7.774        1.559       -0.000        0.000       90.000
   7.000        8.555        1.561       -0.000        0.000       90.000
   7.500        9.336        1.563       -0.000        0.000       90.000
   8.000       10.117        1.563       -0.000        0.000       90.000
   8.500       10.899        1.564       -0.000        0.000       90.000
   9.000       11.681        1.564       -0.000        0.000       90.000
   9.330       12.197        1.564       -0.000        0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
----------------------------------------------------------------------
   Time         Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
   (sec)        (m)          (m/s)        (m/s)        (rad/s)      (deg)
 --------     --------     --------     --------     --------     -------
   0.000        0.000        1.564       -0.000        0.000       90.000
   0.103        0.106        0.350        0.004       -0.011       89.990
   0.121        0.109        0.047       -0.003        0.008       89.993
```

BURIAL RESULT:

Depth of burial: 0.109   metres

Height protruding: 0.500   metres
Area exposed: 1.723   sq m   (76% of total)
Volume exposed: 0.2246 cu m   (88% of total)

```
************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #5 Core #2      Date,Time: 06-21-2000      11:36:24
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area    (sq m)               2.262
Volume of mine           (cu m)               0.256


-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE2
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------     ---------------    ----------------   --------------------
    1            .02              1872.26             7960
    2            .04              1865.57             15330
    3            .06              1849.93             13900
    4            .08              1859               14240
    5            .1               1862               15720
    6            .14              1915               16550
    7            .18              1913               18410
    8            5                1913               18410
```

WATER PHASE

```
--------------------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
   --------    --------    --------    --------    --------    -------
   0.000       0.000       0.000        0.000      0.000       90.000
   0.510       0.089       0.335       -0.000      0.000       90.000
   1.010       0.330       0.617       -0.000      0.000       90.000
   1.510       0.709       0.893       -0.000      0.000       90.000
   2.010       1.216       1.117       -0.000      0.000       90.000
   2.510       1.818       1.278       -0.000      0.000       90.000
   3.010       2.486       1.386       -0.000      0.000       90.000
   3.510       3.198       1.455       -0.000      0.000       90.000
   4.010       3.938       1.498       -0.000      0.000       90.000
   4.500       4.679       1.524       -0.000      0.000       90.000
   5.000       5.446       1.540       -0.000      0.000       90.000
   5.500       6.219       1.550       -0.000      0.000       90.000
   6.000       6.995       1.556       -0.000      0.000       90.000
   6.500       7.774       1.559       -0.000      0.000       90.000
   7.000       8.555       1.561       -0.000      0.000       90.000
   7.500       9.336       1.563       -0.000      0.000       90.000
   8.000      10.117       1.563       -0.000      0.000       90.000
   8.500      10.899       1.564       -0.000      0.000       90.000
   9.000      11.681       1.564       -0.000      0.000       90.000
   9.330      12.197       1.564       -0.000      0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
   --------    --------    --------    --------    --------    -------
   0.000       0.000       1.564       -0.000      0.000       90.000
   0.100       0.117       0.623        0.001     -0.004       89.996
   0.145       0.131       0.048       -0.004      0.011       89.993
```

BURIAL RESULT:

Depth of burial: 0.131   metres

Height protruding: 0.479   metres
Area exposed: 1.656   sq m   (73% of total)
Volume exposed: 0.2155 cu m   (84% of total)

82

```
*************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL              ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #5 Core #3        Date,Time: 06-21-2000      11:37:02
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                 294.835
Apparent mass in water      (kg)                 31.873
Overall length               (m)                 .8763
Maximum diameter             (m)                 .6096
Length of taper on base      (m)                 0
Minimum taper diameter       (m)                 .6096
Distance of CM from centre  (m)                  0
External surface area     (sq m)                 2.262
Volume of mine            (cu m)                 0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE3
 Layer #     Depth to base(m)  Density (kg/m^3)   Bearing strength(Pa)
 ------      ---------------   ----------------   --------------------
    1            .02              1904.78              12380
    2            .04              1917                 14590
    3            .06              1931                 14950
    4            .08              1839                 20600
    5            .1               1925                 30190
    6            .14              1892                 29670
    7            .18              1886                 28180
    8            5                1886                 28180
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.330	12.197	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.101	0.108	0.341	-0.003	0.008	89.993
0.117	0.111	0.044	-0.002	0.006	89.995

BURIAL RESULT:

Depth of burial: 0.111 metres

Height protruding: 0.499 metres
Area exposed: 1.718 sq m   (76% of total)

Volume exposed: 0.2239 cu m   (88% of total)

```
********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
    DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #6 Core #5        Date,Time: 06-21-2000    13:20:37
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area     (sq m)              2.262
Volume of mine            (cu m)              0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12

Sediment characteristics:  CORE5
```

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	0	0	0
2	.02	1930	10210
3	.04	1957	16980
4	.06	1895	18920
5	.1	1854	20600
6	.14	1966	12670
7	.18	1958	18410
8	.22	1934	14240
9	5	1934	14240

WATER PHASE

```
----------------------------------------------------------------------
    Time         Depth        Vert         Horiz        Ang          Angle
                              Vel          Vel          Vel
    (sec)        (m)          (m/s)        (m/s)        (rad/s)      (deg)
  --------     --------     --------     --------     --------     -------
    0.000        0.000        0.000        0.000        0.000       90.000
    0.510        0.089        0.335       -0.000        0.000       90.000
    1.010        0.330        0.617       -0.000        0.000       90.000
    1.510        0.709        0.893       -0.000        0.000       90.000
    2.010        1.216        1.117       -0.000        0.000       90.000
    2.510        1.818        1.278       -0.000        0.000       90.000
    3.010        2.486        1.386       -0.000        0.000       90.000
    3.510        3.198        1.455       -0.000        0.000       90.000
    4.010        3.938        1.498       -0.000        0.000       90.000
    4.500        4.679        1.524       -0.000        0.000       90.000
    5.000        5.446        1.540       -0.000        0.000       90.000
    5.500        6.219        1.550       -0.000        0.000       90.000
    6.000        6.995        1.556       -0.000        0.000       90.000
    6.500        7.774        1.559       -0.000        0.000       90.000
    7.000        8.555        1.561       -0.000        0.000       90.000
    7.500        9.336        1.563       -0.000        0.000       90.000
    8.000       10.117        1.563       -0.000        0.000       90.000
    8.500       10.899        1.564       -0.000        0.000       90.000
    9.000       11.681        1.564       -0.000        0.000       90.000
    9.140       11.900        1.564       -0.000        0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
----------------------------------------------------------------------
    Time         Depth        Vert         Horiz        Ang          Angle
                              Vel          Vel          Vel
    (sec)        (m)          (m/s)        (m/s)        (rad/s)      (deg)
  --------     --------     --------     --------     --------     -------
    0.000        0.000        1.564       -0.000        0.000       90.000
    0.103        0.109        0.405       -0.000        0.000       89.991
    0.132        0.115        0.012        0.001       -0.004       89.993
```

BURIAL RESULT:

Depth of burial: 0.115 metres

Height protruding: 0.495 metres
Area exposed: 1.706 sq m   (75% of total)
Volume exposed: 0.2223 cu m   (87% of total)

```
************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #6 Core #6        Date,Time: 06-21-2000      13:21:38
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                     294.835
Apparent mass in water      (kg)                     31.873
Overall length              (m)                      .8763
Maximum diameter            (m)                      .6096
Length of taper on base     (m)                      0
Minimum taper diameter      (m)                      .6096
Distance of CM from centre  (m)                      0
External surface area    (sq m)                      2.262
Volume of mine           (cu m)                      0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12

Sediment characteristics:  CORE6
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------  --------------------
    1             .02              1905               2090
    2             .04              1919               22520
    3             .06              1870               29160
    4             .08              1901               27250
    5             .1               1903               31280
    6             .14              1897               17910
    7             5                1897               17910
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.102	0.134	0.000	-0.001	89.993
0.107	0.102	0.035	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.102 metres

Height protruding: 0.508 metres
Area exposed: 1.748 sq m   (77% of total)
Volume exposed: 0.2277 cu m   (89% of total)

```
**********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL         ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #6 Core #7       Date,Time: 06-21-2000     13:22:07
Speed mode: Rigorous
----------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                       (kg)                294.835
Apparent mass in water     (kg)                31.873
Overall length             (m)                 .8763
Maximum diameter           (m)                 .6096
Length of taper on base    (m)                 0
Minimum taper diameter     (m)                 .6096
Distance of CM from centre (m)                 0
External surface area   (sq m)                 2.262
Volume of mine          (cu m)                 0.256


----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE7
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------  --------------------
    1             .02              1830               1080
    2             .04              1882               12670
    3             .06              1921               16120
    4             .08              1942               16980
    5             .1               1878               20020
    6             .14              1941               26360
    7             .18              1915               21220
    8             .22              1856               14950
    9             5                1856               14950
```

WATER PHASE

```
-----------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)        (m)        (m/s)       (m/s)       (rad/s)     (deg)
  --------    --------    --------    --------    --------    -------
   0.000       0.000       0.000       0.000       0.000       90.000
   0.510       0.089       0.335      -0.000       0.000       90.000
   1.010       0.330       0.617      -0.000       0.000       90.000
   1.510       0.709       0.893      -0.000       0.000       90.000
   2.010       1.216       1.117      -0.000       0.000       90.000
   2.510       1.818       1.278      -0.000       0.000       90.000
   3.010       2.486       1.386      -0.000       0.000       90.000
   3.510       3.198       1.455      -0.000       0.000       90.000
   4.010       3.938       1.498      -0.000       0.000       90.000
   4.500       4.679       1.524      -0.000       0.000       90.000
   5.000       5.446       1.540      -0.000       0.000       90.000
   5.500       6.219       1.550      -0.000       0.000       90.000
   6.000       6.995       1.556      -0.000       0.000       90.000
   6.500       7.774       1.559      -0.000       0.000       90.000
   7.000       8.555       1.561      -0.000       0.000       90.000
   7.500       9.336       1.563      -0.000       0.000       90.000
   8.000      10.117       1.563      -0.000       0.000       90.000
   8.500      10.899       1.564      -0.000       0.000       90.000
   9.000      11.681       1.564      -0.000       0.000       90.000
   9.140      11.900       1.564      -0.000       0.000       90.000
Accumulated transverse movement   -0.0 m
```

SEDIMENT PHASE

```
-----------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)        (m)        (m/s)       (m/s)       (rad/s)     (deg)
  --------    --------    --------    --------    --------    -------
   0.000       0.000       1.564      -0.000       0.000       90.000
   0.102       0.120       0.537      -0.001       0.003       89.998
   0.131       0.128       0.041       0.001      -0.002       89.994
```

BURIAL RESULT:

Depth of burial: 0.128   metres

Height protruding: 0.482   metres
Area exposed: 1.665   sq m   (74% of total)
Volume exposed: 0.2168 cu m   (85% of total)

```
********************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #6 Core #8        Date,Time: 06-21-2000      13:22:41
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                     (kg)                   294.835
Apparent mass in water   (kg)                   31.873
Overall length            (m)                   .8763
Maximum diameter          (m)                   .6096
Length of taper on base   (m)                   0
Minimum taper diameter    (m)                   .6096
Distance of CM from centre (m)                  0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        11.887
Temperature (deg C):                    12

Sediment characteristics:  CORE8
 Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     ---------------   ----------------  --------------------
    1            .02              1851                 1920
    2            .04              1917                20020
    3            .06              1961                22520
    4            .08              1925                31280
    5            .1               1936                29160
    6            .14              1938                29160
    7            .18              1914                33640
    8            .22              1841                21850
    9            5                1841                21850
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.105	0.176	-0.003	0.008	89.993
0.110	0.106	0.028	0.001	-0.002	89.993

BURIAL RESULT:

Depth of burial: 0.106 metres

Height protruding: 0.504 metres
Area exposed: 1.735 sq m   (77% of total)
Volume exposed: 0.2261 cu m   (88% of total)

```
*************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #7 Core #5        Date,Time: 06-21-2000      13:23:41
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                         (kg)                   294.835
Apparent mass in water       (kg)                   31.873
Overall length               (m)                    .8763
Maximum diameter             (m)                    .6096
Length of taper on base      (m)                    0
Minimum taper diameter       (m)                    .6096
Distance of CM from centre   (m)                    0
External surface area        (sq m)                 2.262
Volume of mine               (cu m)                 0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE5
 Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     ---------------   ----------------  --------------------
    1          0                 0                   0
    2          .02               1930                10210
    3          .04               1957                16980
    4          .06               1895                18920
    5          .1                1854                20600
    6          .14               1966                12670
    7          .18               1958                18410
    8          .22               1934                14240
    9          5                 1934                14240
```

93

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.330	12.197	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.109	0.405	-0.000	0.000	89.991
0.132	0.115	0.012	0.001	-0.004	89.988

BURIAL RESULT:

Depth of burial: 0.115 metres

Height protruding: 0.495 metres
Area exposed: 1.706 sq m   (75% of total)
Volume exposed: 0.2223 cu m   (87% of total)

94

```
************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #7 Core #6        Date,Time: 06-21-2000    13:24:12
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,      55GALDRM

Mass                        (kg)                   294.835
Apparent mass in water      (kg)                   31.873
Overall length              (m)                    .8763
Maximum diameter            (m)                    .6096
Length of taper on base     (m)                    0
Minimum taper diameter      (m)                    .6096
Distance of CM from centre (m)                     0
External surface area    (sq m)                    2.262
Volume of mine           (cu m)                    0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.192
Temperature (deg C):                    12

Sediment characteristics:  CORE6
  Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------      ---------------   ----------------  --------------------
     1             .02              1905               2090
     2             .04              1919               22520
     3             .06              1870               29160
     4             .08              1901               27250
     5             .1               1903               31280
     6             .14              1897               17910
     7             5                1897               17910
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.330	12.197	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.102	0.134	0.000	-0.001	89.993
0.107	0.102	0.036	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.102 metres

Height protruding: 0.508 metres
Area exposed: 1.748 sq m   (77% of total)
Volume exposed: 0.2277 cu m   (89% of total)

```
*****************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
       DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #7 Core #7        Date,Time: 06-21-2000       13:24:41
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                          (kg)                294.835
Apparent mass in water        (kg)                31.873
Overall length                 (m)                .8763
Maximum diameter               (m)                .6096
Length of taper on base        (m)                0
Minimum taper diameter         (m)                .6096
Distance of CM from centre     (m)                0
External surface area       (sq m)                2.262
Volume of mine               (cu m)               0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE7
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------      ---------------    ----------------   --------------------
    1            .02                 1830                 1080
    2            .04                 1882                12670
    3            .06                 1921                16120
    4            .08                 1942                16980
    5            .1                  1878                20020
    6            .14                 1941                26360
    7            .18                 1915                21220
    8            .22                 1856                14950
    9            5                   1856                14950
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.330	12.197	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.120	0.538	-0.001	0.003	89.998
0.131	0.128	0.041	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.128 metres

Height protruding: 0.482 metres
Area exposed: 1.665 sq m   (74% of total)
Volume exposed: 0.2168 cu m   (85% of total)

```
****************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #7 Core #8       Date,Time: 06-21-2000     13:25:12
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                   294.835
Apparent mass in water      (kg)                   31.873
Overall length              (m)                    .8763
Maximum diameter            (m)                    .6096
Length of taper on base     (m)                    0
Minimum taper diameter      (m)                    .6096
Distance of CM from centre (m)                     0
External surface area     (sq m)                   2.262
Volume of mine            (cu m)                   0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE8
 Layer #      Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------      --------------     ----------------   --------------------
    1            .02              1851                  1920
    2            .04              1917                  20020
    3            .06              1961                  22520
    4            .08              1925                  31280
    5            .1               1936                  29160
    6            .14              1938                  29160
    7            .18              1914                  33640
    8            .22              1841                  21850
    9            5                1841                  21850
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.330	12.197	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.105	0.176	-0.003	0.008	89.993
0.110	0.106	0.028	0.001	-0.002	89.993

BURIAL RESULT:

Depth of burial: 0.106 metres

Height protruding: 0.504 metres
Area exposed: 1.735 sq m   (77% of total)
Volume exposed: 0.2261 cu m   (88% of total)

```
********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
       DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #8 Core #5      Date,Time: 06-21-2000     13:26:13
Speed mode: Rigorous
-------------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                      (kg)              294.835
Apparent mass in water    (kg)              31.873
Overall length             (m)              .8763
Maximum diameter           (m)              .6096
Length of taper on base    (m)              0
Minimum taper diameter     (m)              .6096
Distance of CM from centre (m)              0
External surface area    (sq m)             2.262
Volume of mine           (cu m)             0.256


-------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12

Sediment characteristics:  CORE5
 Layer #      Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------   --------------------
    1          0                 0                   0
    2          .02               1930                10210
    3          .04               1957                16980
    4          .06               1895                18920
    5          .1                1854                20600
    6          .14               1966                12670
    7          .18               1958                18410
    8          .22               1934                14240
    9          5                 1934                14240
```

WATER PHASE

```
------------------------------------------------------------------
   Time        Depth        Vert        Horiz        Ang        Angle
                            Vel          Vel         Vel
  (sec)         (m)        (m/s)        (m/s)      (rad/s)      (deg)
 --------     --------     --------     --------    --------    -------
  0.000        0.000        0.000        0.000       0.000      90.000
  0.510        0.089        0.335       -0.000       0.000      90.000
  1.010        0.330        0.617       -0.000       0.000      90.000
  1.510        0.709        0.893       -0.000       0.000      90.000
  2.010        1.216        1.117       -0.000       0.000      90.000
  2.510        1.818        1.278       -0.000       0.000      90.000
  3.010        2.486        1.386       -0.000       0.000      90.000
  3.510        3.198        1.455       -0.000       0.000      90.000
  4.010        3.938        1.498       -0.000       0.000      90.000
  4.500        4.679        1.524       -0.000       0.000      90.000
  5.000        5.446        1.540       -0.000       0.000      90.000
  5.500        6.219        1.550       -0.000       0.000      90.000
  6.000        6.995        1.556       -0.000       0.000      90.000
  6.500        7.774        1.559       -0.000       0.000      90.000
  7.000        8.555        1.561       -0.000       0.000      90.000
  7.500        9.336        1.563       -0.000       0.000      90.000
  8.000       10.117        1.563       -0.000       0.000      90.000
  8.500       10.899        1.564       -0.000       0.000      90.000
  9.000       11.681        1.564       -0.000       0.000      90.000
  9.140       11.900        1.564       -0.000       0.000      90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
------------------------------------------------------------------
   Time        Depth        Vert        Horiz        Ang        Angle
                            Vel          Vel         Vel
  (sec)         (m)        (m/s)        (m/s)      (rad/s)      (deg)
 --------     --------     --------     --------    --------    -------
  0.000        0.000        1.564       -0.000       0.000      90.000
  0.103        0.109        0.405       -0.000       0.000      89.991
  0.132        0.115        0.012        0.001      -0.004      89.993
```

BURIAL RESULT:

Depth of burial: 0.115   metres

Height protruding: 0.495   metres
Area exposed: 1.706   sq m   (75% of total)
Volume exposed: 0.2223 cu m   (87% of total)

102

```
*********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #8 Core #6        Date,Time: 06-21-2000      13:26:45
Speed mode: Rigorous
---------------------------------------------------------------------
Mine characteristics,        55GALDRM


Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area    (sq m)               2.262
Volume of mine           (cu m)               0.256


---------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          11.887
Temperature (deg C):                      12


Sediment characteristics:  CORE6
  Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
  ------      ---------------    ----------------   --------------------
     1             .02               1905                 2090
     2             .04               1919                22520
     3             .06               1870                29160
     4             .08               1901                27250
     5             .1                1903                31280
     6             .14               1897                17910
     7             5                 1897                17910
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
--------	--------	--------	--------	--------	-------
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
--------	--------	--------	--------	--------	-------
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.102	0.134	0.000	-0.001	89.993
0.107	0.102	0.035	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.102 metres

Height protruding: 0.508 metres
Area exposed: 1.748 sq m   (77% of total)
Volume exposed: 0.2277 cu m   (89% of total)

104

```
**************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #8 Core #7         Date,Time: 06-21-2000      13:27:30
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                    294.835
Apparent mass in water      (kg)                    31.873
Overall length               (m)            ·       .8763
Maximum diameter             (m)                    .6096
Length of taper on base      (m)                    0
Minimum taper diameter       (m)                    .6096
Distance of CM from centre   (m)                    0
External surface area    (sq m)                     2.262
Volume of mine          (cu m)                      0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE7
```

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1830	1080
2	.04	1882	12670
3	.06	1921	16120
4	.08	1942	16980
5	.1	1878	20020
6	.14	1941	26360
7	.18	1915	21220
8	.22	1856	14950
9	5	1856	14950

WATER PHASE

```
-----------------------------------------------------------------
    Time        Depth       Vert        Horiz       Ang         Angle
                            Vel         Vel         Vel
    (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
    --------    --------    --------    --------    --------    -------
    0.000       0.000       0.000       0.000       0.000       90.000
    0.510       0.089       0.335      -0.000       0.000       90.000
    1.010       0.330       0.617      -0.000       0.000       90.000
    1.510       0.709       0.893      -0.000       0.000       90.000
    2.010       1.216       1.117      -0.000       0.000       90.000
    2.510       1.818       1.278      -0.000       0.000       90.000
    3.010       2.486       1.386      -0.000       0.000       90.000
    3.510       3.198       1.455      -0.000       0.000       90.000
    4.010       3.938       1.498      -0.000       0.000       90.000
    4.500       4.679       1.524      -0.000       0.000       90.000
    5.000       5.446       1.540      -0.000       0.000       90.000
    5.500       6.219       1.550      -0.000       0.000       90.000
    6.000       6.995       1.556      -0.000       0.000       90.000
    6.500       7.774       1.559      -0.000       0.000       90.000
    7.000       8.555       1.561      -0.000       0.000       90.000
    7.500       9.336       1.563      -0.000       0.000       90.000
    8.000      10.117       1.563      -0.000       0.000       90.000
    8.500      10.899       1.564      -0.000       0.000       90.000
    9.000      11.681       1.564      -0.000       0.000       90.000
    9.140      11.900       1.564      -0.000       0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
-----------------------------------------------------------------
    Time        Depth       Vert        Horiz       Ang         Angle
                            Vel         Vel         Vel
    (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
    --------    --------    --------    --------    --------    -------
    0.000       0.000       1.564      -0.000       0.000       90.000
    0.102       0.120       0.537      -0.001       0.003       89.998
    0.131       0.128       0.041       0.001      -0.002       89.994
```

BURIAL RESULT:

Depth of burial: 0.128   metres

Height protruding: 0.482   metres
Area exposed: 1.665   sq m   (74% of total)
Volume exposed: 0.2168 cu m   (85% of total)

```
**************************************************************
******       NCSC/DSE IMPACT BURIAL PREDICTION MODEL       ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #8 Core #8        Date,Time: 06-21-2000      13:28:08
Speed mode: Rigorous
-------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                         (kg)                 294.835
Apparent mass in water       (kg)                 31.873
Overall length               (m)                  .8763
Maximum diameter             (m)                  .6096
Length of taper on base      (m)                  0
Minimum taper diameter       (m)                  .6096
Distance of CM from centre   (m)                  0
External surface area    (sq m)                   2.262
Volume of mine           (cu m)                   0.256


-------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):          .          12
```

Sediment characteristics: CORE8

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1851	1920
2	.04	1917	20020
3	.06	1961	22520
4	.08	1925	31280
5	.1	1936	29160
6	.14	1938	29160
7	.18	1914	33640
8	.22	1841	21850
9	5	1841	21850

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.105	0.176	-0.003	0.008	89.993
0.110	0.106	0.028	0.001	-0.002	89.993

BURIAL RESULT:

Depth of burial: 0.106   metres

Height protruding: 0.504   metres
Area exposed: 1.735 sq m   (77% of total)
Volume exposed: 0.2261 cu m   (88% of total)

108

```
*********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #9 Core #5      Date,Time: 06-21-2000     13:28:57
Speed mode: Rigorous
---------------------------------------------------------------------
Mine characteristics,      55GALDRM

Mass                       (kg)                     294.835
Apparent mass in water     (kg)                     31.873
Overall length             (m)                      .8763
Maximum diameter           (m)                      .6096
Length of taper on base    (m)                      0
Minimum taper diameter     (m)                      .6096
Distance of CM from centre (m)                      0
External surface area    (sq m)                     2.262
Volume of mine           (cu m)                     0.256


---------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE5
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------     ---------------    ----------------   --------------------
    1          0                  0                     0
    2          .02               1930                  10210
    3          .04               1957                  16980
    4          .06               1895                  18920
    5          .1                1854                  20600
    6          .14               1966                  12670
    7          .18               1958                  18410
    8          .22               1934                  14240
    9          5                 1934                  14240
```

WATER PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
    (sec)        (m)         (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
    0.000       0.000        0.000        0.000        0.000       90.000
    0.510       0.089        0.335       -0.000        0.000       90.000
    1.010       0.330        0.617       -0.000        0.000       90.000
    1.510       0.709        0.893       -0.000        0.000       90.000
    2.010       1.216        1.117       -0.000        0.000       90.000
    2.510       1.818        1.278       -0.000        0.000       90.000
    3.010       2.486        1.386       -0.000        0.000       90.000
    3.510       3.198        1.455       -0.000        0.000       90.000
    4.010       3.938        1.498       -0.000        0.000       90.000
    4.500       4.679        1.524       -0.000        0.000       90.000
    5.000       5.446        1.540       -0.000        0.000       90.000
    5.500       6.219        1.550       -0.000        0.000       90.000
    6.000       6.995        1.556       -0.000        0.000       90.000
    6.500       7.774        1.559       -0.000        0.000       90.000
    7.000       8.555        1.561       -0.000        0.000       90.000
    7.500       9.336        1.563       -0.000        0.000       90.000
    8.000      10.117        1.563       -0.000        0.000       90.000
    8.500      10.899        1.564       -0.000        0.000       90.000
    9.000      11.681        1.564       -0.000        0.000       90.000
    9.140      11.900        1.564       -0.000        0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert         Horiz        Ang          Angle
                             Vel          Vel          Vel
    (sec)        (m)         (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
    0.000       0.000        1.564       -0.000        0.000       90.000
    0.103       0.109        0.405       -0.000        0.000       89.991
    0.132       0.115        0.012        0.001       -0.004       89.993
```

BURIAL RESULT:

Depth of burial: 0.115   metres

Height protruding: 0.495   metres
Area exposed: 1.706   sq m   (75% of total)
Volume exposed: 0.2223 cu m   (87% of total)

110

```
*******************************************************************
******      NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
    DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #9 Core #6       Date,Time: 06-21-2000     13:29:31
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                        (kg)                294.835
Apparent mass in water      (kg)                31.873
Overall length              (m)                 .8763
Maximum diameter            (m)                 .6096
Length of taper on base     (m)                 0
Minimum taper diameter      (m)                 .6096
Distance of CM from centre  (m)                 0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256
          .

-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        11.887
Temperature (deg C):                    12


Sediment characteristics:  CORE6
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     ---------------   ----------------  --------------------
    1           .02              1905                 2090
    2           .04              1919                 22520
    3           .06              1870                 29160
    4           .08              1901                 27250
    5           .1               1903                 31280
    6           .14              1897                 17910
    7           5                1897                 17910
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
--------	--------	--------	--------	--------	-------
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	.6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
--------	--------	--------	--------	--------	-------
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.102	0.134	0.000	-0.001	89.993
0.107	0.102	0.035	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.102   metres

Height protruding: 0.508   metres
Area exposed: 1.748 sq m   (77% of total)
Volume exposed: 0.2277 cu m   (89% of total)

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* * * * * *         NCSC/DSE IMPACT BURIAL PREDICTION MODEL              * * * * * *
       DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #9 Core #7       Date,Time: 06-21-2000     13:30:00
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                         (kg)               294.835
Apparent mass in water       (kg)               31.873
Overall length               (m)                .8763
Maximum diameter             (m)                .6096
Length of taper on base      (m)                0
Minimum taper diameter       (m)                .6096
Distance of CM from centre   (m)                0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)               0
Horiz vel (rightward pos)                  0
Angle(0 vertical,90 horizontal)            90
Rotation rate(rad/sec cl'wise)             0
Water depth (m):                           11.887
Temperature (deg C):                       12

Sediment characteristics:  CORE7
  Layer #     Depth to base(m)  Density (kg/m^3)   Bearing strength(Pa)
  ------      ---------------   ----------------   --------------------
     1            .02              1830                1080
     2            .04              1882                12670
     3            .06              1921                16120
     4            .08              1942                16980
     5            .1               1878                20020
     6            .14              1941                26360
     7            .18              1915                21220
     8            .22              1856                14950
     9            5                1856                14950
```

WATER PHASE

```
--------------------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
  --------    --------    --------    --------    --------    -------
   0.000       0.000       0.000       0.000       0.000       90.000
   0.510       0.089       0.335      -0.000       0.000       90.000
   1.010       0.330       0.617      -0.000       0.000       90.000
   1.510       0.709       0.893      -0.000       0.000       90.000
   2.010       1.216       1.117      -0.000       0.000       90.000
   2.510       1.818       1.278      -0.000       0.000       90.000
   3.010       2.486       1.386      -0.000       0.000       90.000
   3.510       3.198       1.455      -0.000       0.000       90.000
   4.010       3.938       1.498      -0.000       0.000       90.000
   4.500       4.679       1.524      -0.000       0.000       90.000
   5.000       5.446       1.540      -0.000       0.000       90.000
   5.500       6.219       1.550      -0.000       0.000       90.000
   6.000       6.995       1.556      -0.000       0.000       90.000
   6.500       7.774       1.559      -0.000       0.000       90.000
   7.000       8.555       1.561      -0.000       0.000       90.000
   7.500       9.336       1.563      -0.000       0.000       90.000
   8.000      10.117       1.563      -0.000       0.000       90.000
   8.500      10.899       1.564      -0.000       0.000       90.000
   9.000      11.681       1.564      -0.000       0.000       90.000
   9.140      11.900       1.564      -0.000       0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
   Time        Depth       Vert        Horiz       Ang         Angle
                           Vel         Vel         Vel
   (sec)       (m)         (m/s)       (m/s)       (rad/s)     (deg)
  --------    --------    --------    --------    --------    -------
   0.000       0.000       1.564      -0.000       0.000       90.000
   0.102       0.120       0.537      -0.001       0.003       89.998
   0.131       0.128       0.041       0.001      -0.002       89.994
```

BURIAL RESULT:

Depth of burial: 0.128   metres

Height protruding: 0.482   metres
Area exposed: 1.665   sq m   (74% of total)
Volume exposed: 0.2168 cu m   (85% of total)

```
****************************************************************
******      NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #9 Core #8       Date,Time: 06-21-2000      13:30:39
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                        (kg)                  294.835
Apparent mass in water      (kg)                  31.873
Overall length              (m)                   .8763
Maximum diameter            (m)                   .6096
Length of taper on base     (m)                   0
Minimum taper diameter      (m)                   .6096
Distance of CM from centre  (m)                   0
External surface area    (sq m)                   2.262
Volume of mine           (cu m)                   0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)             0
Horiz vel (rightward pos)                0
Angle(0 vertical,90 horizontal)          90
Rotation rate(rad/sec cl'wise)           0
Water depth (m):                         11.887
Temperature (deg C):                     12

Sediment characteristics:  CORE8
 Layer #     Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
 ------      ---------------    ---------------    --------------------
    1            .02               1851                 1920
    2            .04               1917                 20020
    3            .06               1961                 22520
    4            .08               1925                 31280
    5            .1                1936                 29160
    6            .14               1938                 29160
    7            .18               1914                 33640
    8            .22               1841                 21850
    9           5                  1841                 21850
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.140	11.900	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.105	0.176	-0.003	0.008	89.993
0.110	0.106	0.028	0.001	-0.002	89.993

BURIAL RESULT:

Depth of burial: 0.106 metres

Height protruding: 0.504 metres
Area exposed: 1.735 sq m   (77% of total)
Volume exposed: 0.2261 cu m   (88% of total)

```
******************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
        DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #10 Core #5      Date,Time: 06-21-2000     13:31:32
Speed mode: Rigorous
------------------------------------------------------------------
Mine characteristics,       55GALDRM


Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length               (m)              .8763
Maximum diameter             (m)              .6096
Length of taper on base      (m)              0
Minimum taper diameter       (m)              .6096
Distance of CM from centre  (m)               0
External surface area     (sq m)              2.262
Volume of mine            (cu m)              0.256


------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)               0
Horiz vel (rightward pos)                  0
Angle(0 vertical,90 horizontal)            90
Rotation rate(rad/sec cl'wise)             0
Water depth (m):                           12.497
Temperature (deg C):                       12


Sediment characteristics:  CORE5
  Layer #    Depth to base(m)  Density (kg/m^3)   Bearing strength(Pa)
  ------    ---------------   ----------------   --------------------
     1        0                0                   0
     2        .02              1930                10210
     3        .04              1957                16980
     4        .06              1895                18920
     5        .1               1854                20600
     6        .14              1966                12670
     7        .18              1958                18410
     8        .22              1934               · 14240
     9        5                1934                14240
```

WATER PHASE

```
-----------------------------------------------------------------------
   Time        Depth        Vert        Horiz         Ang        Angle
                            Vel          Vel          Vel
   (sec)        (m)        (m/s)        (m/s)       (rad/s)      (deg)
 --------    --------    --------    ---------    ---------    -------
   0.000       0.000       0.000        0.000        0.000      90.000
   0.510       0.089       0.335       -0.000        0.000      90.000
   1.010       0.330       0.617       -0.000        0.000      90.000
   1.510       0.709       0.893       -0.000        0.000      90.000
   2.010       1.216       1.117       -0.000        0.000      90.000
   2.510       1.818       1.278       -0.000        0.000      90.000
   3.010       2.486       1.386       -0.000        0.000      90.000
   3.510       3.198       1.455       -0.000        0.000      90.000
   4.010       3.938       1.498       -0.000        0.000      90.000
   4.500       4.679       1.524       -0.000        0.000      90.000
   5.000       5.446       1.540       -0.000        0.000      90.000
   5.500       6.219       1.550       -0.000        0.000      90.000
   6.000       6.995       1.556       -0.000        0.000      90.000
   6.500       7.774       1.559       -0.000        0.000      90.000
   7.000       8.555       1.561       -0.000        0.000      90.000
   7.500       9.336       1.563       -0.000        0.000      90.000
   8.000      10.117       1.563       -0.000        0.000      90.000
   8.500      10.899       1.564       -0.000        0.000      90.000
   9.000      11.681       1.564       -0.000        0.000      90.000
   9.500      12.463       1.564       -0.000        0.000      90.000
   9.530      12.510       1.564       -0.000        0.000      90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
-----------------------------------------------------------------------
   Time        Depth        Vert        Horiz         Ang        Angle
                            Vel          Vel          Vel
   (sec)        (m)        (m/s)        (m/s)       (rad/s)      (deg)
 --------    --------    --------    ---------    ---------    -------
   0.000       0.000       1.564       -0.000        0.000      90.000
   0.102       0.109       0.405       -0.000        0.000      89.991
   0.132       0.115       0.012        0.001       -0.004      89.988
```

BURIAL RESULT:

Depth of burial: 0.115   metres

Height protruding: 0.495   metres
Area exposed: 1.706   sq m   (75% of total)
Volume exposed: 0.2223 cu m   (87% of total)

118

```
************************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #10 Core #6       Date,Time: 06-21-2000      13:32:01
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area     (sq m)              2.262
Volume of mine            (cu m)              0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE6
```

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1905	2090
2	.04	1919	22520
3	.06	1870	29160
4	.08	1901	27250
5	.1	1903	31280
6	.14	1897	17910
7	5	1897	17910

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.102	0.134	0.000	-0.001	89.993
0.107	0.102	0.036	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.102 metres

Height protruding: 0.508 metres
Area exposed: 1.748 sq m   (77% of total)
Volume exposed: 0.2277 cu m   (89% of total)

```
*****************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #10 Core #7      Date,Time: 06-21-2000     13:32:29
Speed mode: Rigorous
----------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length               (m)              .8763
Maximum diameter             (m)              .6096
Length of taper on base      (m)              0
Minimum taper diameter       (m)              .6096
Distance of CM from centre  (m)              0
External surface area    (sq m)              2.262
Volume of mine           (cu m)              0.256


----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)               0
Horiz vel (rightward pos)                  0
Angle(0 vertical,90 horizontal)            90
Rotation rate(rad/sec cl'wise)             0
Water depth (m):                           12.497
Temperature (deg C):                       12

Sediment characteristics:  CORE7
  Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------      --------------    ----------------  --------------------
     1            .02              1830              1080
     2            .04              1882              12670
     3            .06              1921              16120
     4            .08              1942              16980
     5            .1               1878              20020
     6            .14              1941              26360
     7            .18              1915              21220
     8            .22              1856              14950
     9            5                1856              14950
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.120	0.538	-0.001	0.003	89.998
0.131	0.128	0.041	0.001	-0.002	89.994

BURIAL RESULT:

Depth of burial: 0.128   metres

Height protruding: 0.482   metres
Area exposed: 1.665 sq m   (74% of total)
Volume exposed: 0.2168 cu m   (85% of total)

```
************************************************************************
******      NCSC/DSE IMPACT BURIAL PREDICTION MODEL         ******
    DOTSE development version IMPACTD1 with 100 Layers,20 March 1997
```

Run name: Drop #10 Core #8   Date,Time: 06-21-2000   13:32:57
Speed mode: Rigorous

Mine characteristics,   55GALDRM

Mass	(kg)	294.835
Apparent mass in water	(kg)	31.873
Overall length	(m)	.8763
Maximum diameter	(m)	.6096
Length of taper on base	(m)	0
Minimum taper diameter	(m)	.6096
Distance of CM from centre	(m)	0
External surface area	(sq m)	2.262
Volume of mine	(cu m)	0.256

RELEASE CONDITIONS

Vert vel (downward positive)	0
Horiz vel (rightward pos)	0
Angle(0 vertical,90 horizontal)	90
Rotation rate(rad/sec cl'wise)	0
Water depth (m):	12.497
Temperature (deg C):	12

Sediment characteristics: CORE8

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1851	1920
2	.04	1917	20020
3	.06	1961	22520
4	.08	1925	31280
5	.1	1936	29160
6	.14	1938	29160
7	.18	1914	33640
8	.22	1841	21850
9	5	1841	21850

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.102	0.105	0.176	-0.003	0.008	89.993
0.110	0.106	0.028	0.001	-0.002	89.993

BURIAL RESULT:

Depth of burial: 0.106 metres

Height protruding: 0.504 metres
Area exposed: 1.735 sq m   (77% of total)

Volume exposed: 0.2261 cu m   (88% of total)

```
**********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL         ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #11 Core #9     Date,Time: 06-22-2000     09:35:56
Speed mode: Rigorous
----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                  294.835
Apparent mass in water      (kg)                  31.873
Overall length              (m)                   .8763
Maximum diameter            (m)                   .6096
Length of taper on base     (m)                   0
Minimum taper diameter      (m)                   .6096
Distance of CM from centre  (m)                   0
External surface area    (sq m)                   2.262
Volume of mine           (cu m)                   0.256


----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.192
Temperature (deg C):                    12

Sediment characteristics:  CORE9
  Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------      ---------------   ----------------  --------------------
     1             .02              1842                1880
     2             .04              1922                16550
     3             .06              1936                21220
     4             .08              1941                16980
     5             .1               2034                18920
     6             .14              2001                13900
     7             .18              1922                20600
     8             .22              1930                23220
     9             5                1930                23220
```

```
WATER PHASE

-------------------------------------------------------------------------
   Time       Depth       Vert        Horiz       Ang         Angle
                          Vel         Vel         Vel
   (sec)      (m)         (m/s)       (m/s)       (rad/s)     (deg)
 --------   --------    --------    --------    --------    -------
   0.000      0.000       0.000       0.000       0.000      90.000
   0.510      0.089       0.335      -0.000       0.000      90.000
   1.010      0.330       0.617      -0.000       0.000      90.000
   1.510      0.709       0.893      -0.000       0.000      90.000
   2.010      1.216       1.117      -0.000       0.000      90.000
   2.510      1.818       1.278      -0.000       0.000      90.000
   3.010      2.486       1.386      -0.000       0.000      90.000
   3.510      3.198       1.455      -0.000       0.000      90.000
   4.010      3.938       1.498      -0.000       0.000      90.000
   4.500      4.679       1.524      -0.000       0.000      90.000
   5.000      5.446       1.540      -0.000       0.000      90.000
   5.500      6.219       1.550      -0.000       0.000      90.000
   6.000      6.995       1.556      -0.000       0.000      90.000
   6.500      7.774       1.559      -0.000       0.000      90.000
   7.000      8.555       1.561      -0.000       0.000      90.000
   7.500      9.336       1.563      -0.000       0.000      90.000
   8.000     10.117       1.563      -0.000       0.000      90.000
   8.500     10.899       1.564      -0.000       0.000      90.000
   9.000     11.681       1.564      -0.000       0.000      90.000
   9.330     12.197       1.564      -0.000       0.000      90.000
Accumulated transverse movement    -0.0 m
```

```
SEDIMENT PHASE

-------------------------------------------------------------------------
   Time       Depth       Vert        Horiz       Ang         Angle
                          Vel         Vel         Vel
   (sec)      (m)         (m/s)       (m/s)       (rad/s)     (deg)
 --------   --------    --------    --------    --------    -------
   0.000      0.000       1.564      -0.000       0.000      90.000
   0.103      0.116       0.516       0.001      -0.002      89.993
   0.141      0.126       0.023       0.003      -0.009      89.993
```

BURIAL RESULT:

Depth of burial: 0.126 metres

Height protruding: 0.484 metres
Area exposed: 1.671 sq m   (74% of total)
Volume exposed: 0.2177 cu m   (85% of total)

```
*************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #11 Core #10     Date,Time: 06-22-2000     09:36:37
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,      55GALDRM


Mass                      (kg)                    294.835
Apparent mass in water    (kg)                    31.873
Overall length             (m)                    .8763
Maximum diameter           (m)                    .6096
Length of taper on base    (m)                    0
Minimum taper diameter     (m)                    .6096
Distance of CM from centre (m)                    0
External surface area    (sq m)                   2.262
Volume of mine           (cu m)                   0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.192
Temperature (deg C):                      12

Sediment characteristics:  CORE10
 Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     ---------------   ----------------  --------------------
    1         0                 0                   0
    2         .02              1862                1800
    3         .04              1870               24720
    4         .06              1862               32430
    5         .08              1905               23950
    6         .1               1879               31280
    7         .14              1876               29160
    8         .18              1903               20600
    9         5                1903               20600
```

WATER PHASE

```
-----------------------------------------------------------------------
   Time       Depth       Vert       Horiz      Ang        Angle
                          Vel        Vel        Vel
  (sec)        (m)        (m/s)      (m/s)      (rad/s)    (deg)
  --------   --------    --------   --------   --------   -------
   0.000      0.000       0.000      0.000      0.000     90.000
   0.510      0.089       0.335     -0.000      0.000     90.000
   1.010      0.330       0.617     -0.000      0.000     90.000
   1.510      0.709       0.893     -0.000      0.000     90.000
   2.010      1.216       1.117     -0.000      0.000     90.000
   2.510      1.818       1.278     -0.000      0.000     90.000
   3.010      2.486       1.386     -0.000      0.000     90.000
   3.510      3.198       1.455     -0.000      0.000     90.000
   4.010      3.938       1.498     -0.000      0.000     90.000
   4.500      4.679       1.524     -0.000      0.000     90.000
   5.000      5.446       1.540     -0.000      0.000     90.000
   5.500      6.219       1.550     -0.000      0.000     90.000
   6.000      6.995       1.556     -0.000      0.000     90.000
   6.500      7.774       1.559     -0.000      0.000     90.000
   7.000      8.555       1.561     -0.000      0.000     90.000
   7.500      9.336       1.563     -0.000      0.000     90.000
   8.000     10.117       1.563     -0.000      0.000     90.000
   8.500     10.899       1.564     -0.000      0.000     90.000
   9.000     11.681       1.564     -0.000      0.000     90.000
   9.330     12.197       1.564     -0.000      0.000     90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
-----------------------------------------------------------------------
   Time       Depth       Vert       Horiz      Ang        Angle
                          Vel        Vel        Vel
  (sec)        (m)        (m/s)      (m/s)      (rad/s)    (deg)
  --------   --------    --------   --------   --------   -------
   0.000      0.000       1.564     -0.000      0.000     90.000
   0.100      0.100       0.140      0.003     -0.009     89.991
   0.105      0.100       0.041     -0.003      0.008     89.993
```

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.509   metres
Area exposed: 1.753   sq m   (78% of total)
Volume exposed: 0.2283 cu m   (89% of total)

```
*******************************************************************
******      NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
    DOTSE development version IMPACTD1 with 100 Layers,20 March 1997


Run name: Drop #12 Core #9     Date,Time: 06-22-2000     09:37:26
Speed mode: Rigorous
-------------------------------------------------------------------
Mine characteristics,      55GALDRM


Mass                      (kg)              294.835
Apparent mass in water    (kg)              31.873
Overall length            (m)               .8763
Maximum diameter          (m)               .6096
Length of taper on base   (m)               0
Minimum taper diameter    (m)               .6096
Distance of CM from centre (m)              0
External surface area    (sq m)             2.262
Volume of mine           (cu m)             0.256


-------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)           0
Horiz vel (rightward pos)              0
Angle(0 vertical,90 horizontal)        90
Rotation rate(rad/sec cl'wise)         0
Water depth (m):                       12.497
Temperature (deg C):                   12
```

Sediment characteristics: CORE9

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1842	1880
2	.04	1922	16550
3	.06	1936	21220
4	.08	1941	16980
5	.1	2034	18920
6	.14	2001	13900
7	.18	1922	20600
8	.22	1930	23220
9	5	1930	23220

WATER PHASE

```
------------------------------------------------------------------------
   Time        Depth        Vert        Horiz       Ang         Angle
                            Vel         Vel         Vel
   (sec)       (m)          (m/s)       (m/s)       (rad/s)     (deg)
 --------    ---------     --------    --------    --------    -------
   0.000       0.000        0.000       0.000       0.000      90.000
   0.510       0.089        0.335      -0.000       0.000      90.000
   1.010       0.330        0.617      -0.000       0.000      90.000
   1.510       0.709        0.893      -0.000       0.000      90.000
   2.010       1.216        1.117      -0.000       0.000      90.000
   2.510       1.818        1.278      -0.000       0.000      90.000
   3.010       2.486        1.386      -0.000       0.000      90.000
   3.510       3.198        1.455      -0.000       0.000      90.000
   4.010       3.938        1.498      -0.000       0.000      90.000
   4.500       4.679        1.524      -0.000       0.000      90.000
   5.000       5.446        1.540      -0.000       0.000      90.000
   5.500       6.219        1.550      -0.000       0.000      90.000
   6.000       6.995        1.556      -0.000       0.000      90.000
   6.500       7.774        1.559      -0.000       0.000      90.000
   7.000       8.555        1.561      -0.000       0.000      90.000
   7.500       9.336        1.563      -0.000       0.000      90.000
   8.000      10.117        1.563      -0.000       0.000      90.000
   8.500      10.899        1.564      -0.000       0.000      90.000
   9.000      11.681        1.564      -0.000       0.000      90.000
   9.500      12.463        1.564      -0.000       0.000      90.000
   9.530      12.510        1.564      -0.000       0.000      90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
------------------------------------------------------------------------
   Time        Depth        Vert        Horiz       Ang         Angle
                            Vel         Vel         Vel
   (sec)       (m)          (m/s)       (m/s)       (rad/s)     (deg)
 --------    ---------     --------    --------    --------    -------
   0.000       0.000        1.564      -0.000       0.000      90.000
   0.103       0.116        0.516       0.001      -0.002      89.993
   0.141       0.126        0.023       0.003      -0.009      89.993
```

BURIAL RESULT:

Depth of burial: 0.126   metres

Height protruding: 0.484   metres
Area exposed: 1.671   sq m   (74% of total)
Volume exposed: 0.2177 cu m   (85% of total)

```
*************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #12 Core #10     Date,Time: 06-22-2000     09:37:55
Speed mode: Rigorous
-----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                      (kg)                    294.835
Apparent mass in water    (kg)                    31.873
Overall length            (m)                     .8763
Maximum diameter          (m)                     .6096
Length of taper on base   (m)                     0
Minimum taper diameter    (m)                     .6096
Distance of CM from centre (m)                    0
External surface area     (sq m)                  2.262
Volume of mine            (cu m)                  0.256


-----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE10
  Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------      ---------------   ----------------  --------------------
     1            0                 0                    0
     2            .02              1862                 1800
     3            .04              1870                24720
     4            .06              1862                32430
     5            .08              1905                23950
     6            .1               1879                31280
     7            .14              1876                29160
     8            .18              1903                20600
     9            5                1903                20600
```

WATER PHASE

```
-------------------------------------------------------------------
   Time        Depth        Vert        Horiz        Ang         Angle
                            Vel         Vel          Vel
   (sec)       (m)          (m/s)       (m/s)        (rad/s)     (deg)
 --------    --------     --------    --------     --------     -------
   0.000       0.000        0.000       0.000        0.000       90.000
   0.510       0.089        0.335      -0.000        0.000       90.000
   1.010       0.330        0.617      -0.000        0.000       90.000
   1.510       0.709        0.893      -0.000        0.000       90.000
   2.010       1.216        1.117      -0.000        0.000       90.000
   2.510       1.818        1.278      -0.000        0.000       90.000
   3.010       2.486        1.386      -0.000        0.000       90.000
   3.510       3.198        1.455      -0.000        0.000       90.000
   4.010       3.938        1.498      -0.000        0.000       90.000
   4.500       4.679        1.524      -0.000        0.000       90.000
   5.000       5.446        1.540      -0.000        0.000       90.000
   5.500       6.219        1.550      -0.000        0.000       90.000
   6.000       6.995        1.556      -0.000        0.000       90.000
   6.500       7.774        1.559      -0.000        0.000       90.000
   7.000       8.555        1.561      -0.000        0.000       90.000
   7.500       9.336        1.563      -0.000        0.000       90.000
   8.000      10.117        1.563      -0.000        0.000       90.000
   8.500      10.899        1.564      -0.000        0.000       90.000
   9.000      11.681        1.564      -0.000        0.000       90.000
   9.500      12.463        1.564      -0.000        0.000       90.000
   9.530      12.510        1.564      -0.000        0.000       90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
-------------------------------------------------------------------
   Time        Depth        Vert        Horiz        Ang         Angle
                            Vel         Vel          Vel
   (sec)       (m)          (m/s)       (m/s)        (rad/s)     (deg)
 --------    --------     --------    --------     --------     -------
   0.000       0.000        1.564      -0.000        0.000       90.000
   0.100       0.100        0.140       0.003       -0.009       89.991
   0.105       0.100        0.041      -0.003        0.008       89.993
```

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.509   metres
Area exposed: 1.753   sq m   (77% of total)
Volume exposed: 0.2283 cu m   (89% of total)

132

```
****************************************************************
******         NCSC/DSE IMPACT BURIAL PREDICTION MODEL           ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #13 Core #9      Date,Time: 06-22-2000     09:38:36
Speed mode: Rigorous
----------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                       (kg)              294.835
Apparent mass in water     (kg)               31.873
Overall length             (m)                 .8763
Maximum diameter           (m)                 .6096
Length of taper on base    (m)                0
Minimum taper diameter     (m)                 .6096
Distance of CM from centre (m)                0
External surface area    (sq m)               2.262
Volume of mine           (cu m)               0.256


----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE9
  Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
  ------     ---------------   ----------------  --------------------
     1            .02               1842               1880
     2            .04               1922              16550
     3            .06               1936              21220
     4            .08               1941              16980
     5            .1                2034              18920
     6            .14               2001              13900
     7            .18               1922              20600
     8            .22               1930              23220
     9           5                  1930              23220
```

WATER PHASE

```
--------------------------------------------------------------------
   Time        Depth        Vert        Horiz       Ang        Angle
                            Vel         Vel         Vel
   (sec)        (m)         (m/s)       (m/s)       (rad/s)    (deg)
 --------    ---------    ---------   ---------   ---------   -------
   0.000       0.000        0.000       0.000       0.000     90.000
   0.510       0.089        0.335      -0.000       0.000     90.000
   1.010       0.330        0.617      -0.000       0.000     90.000
   1.510       0.709        0.893      -0.000       0.000     90.000
   2.010       1.216        1.117      -0.000       0.000     90.000
   2.510       1.818        1.278      -0.000       0.000     90.000
   3.010       2.486        1.386      -0.000       0.000     90.000
   3.510       3.198        1.455      -0.000       0.000     90.000
   4.010       3.938        1.498      -0.000       0.000     90.000
   4.500       4.679        1.524      -0.000       0.000     90.000
   5.000       5.446        1.540      -0.000       0.000     90.000
   5.500       6.219        1.550      -0.000       0.000     90.000
   6.000       6.995        1.556      -0.000       0.000     90.000
   6.500       7.774        1.559      -0.000       0.000     90.000
   7.000       8.555        1.561      -0.000       0.000     90.000
   7.500       9.336        1.563      -0.000       0.000     90.000
   8.000      10.117        1.563      -0.000       0.000     90.000
   8.500      10.899        1.564      -0.000       0.000     90.000
   9.000      11.681        1.564      -0.000       0.000     90.000
   9.500      12.463        1.564      -0.000       0.000     90.000
   9.530      12.510        1.564      -0.000       0.000     90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------
   Time        Depth        Vert        Horiz       Ang        Angle
                            Vel         Vel         Vel
   (sec)        (m)         (m/s)       (m/s)       (rad/s)    (deg)
 --------    ---------    ---------   ---------   ---------   -------
   0.000       0.000        1.564      -0.000       0.000     90.000
   0.103       0.116        0.516       0.001      -0.002     89.993
   0.141       0.126        0.023       0.003      -0.009     89.993
```

BURIAL RESULT:

Depth of burial: 0.126   metres

Height protruding: 0.484   metres
Area exposed: 1.671   sq m   (74% of total)
Volume exposed: 0.2177 cu m   (85% of total)

```
*********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #13 Core #10    Date,Time: 06-22-2000    09:39:05
Speed mode: Rigorous
--------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                    (kg)                    294.835
Apparent mass in water  (kg)                    31.873
Overall length          (m)                     .8763
Maximum diameter        (m)                     .6096
Length of taper on base (m)                     0
Minimum taper diameter  (m)                     .6096
Distance of CM from centre (m)                  0
External surface area   (sq m)                  2.262
Volume of mine          (cu m)                  0.256


--------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)          0
Horiz vel (rightward pos)             0
Angle(0 vertical,90 horizontal)       90
Rotation rate(rad/sec cl'wise)        0
Water depth (m):                      12.497
Temperature (deg C):                  12

Sediment characteristics:  CORE10
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------  --------------------
    1        0                 0                 0
    2        .02               1862              1800
    3        .04               1870              24720
    4        .06               1862              32430
    5        .08               1905              23950
    6        .1                1879              31280
    7        .14               1876              29160
    8        .18               1903              20600
    9        5                 1903              20600
```

WATER PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang        Angle
                             Vel         Vel          Vel
    (sec)       (m)          (m/s)       (m/s)        (rad/s)    (deg)
    --------    --------     --------    --------     --------   -------
    0.000       0.000        0.000        0.000        0.000      90.000
    0.510       0.089        0.335       -0.000        0.000      90.000
    1.010       0.330        0.617       -0.000        0.000      90.000
    1.510       0.709        0.893       -0.000        0.000      90.000
    2.010       1.216        1.117       -0.000        0.000      90.000
    2.510       1.818        1.278       -0.000        0.000      90.000
    3.010       2.486        1.386       -0.000        0.000      90.000
    3.510       3.198        1.455       -0.000        0.000      90.000
    4.010       3.938        1.498       -0.000        0.000      90.000
    4.500       4.679        1.524       -0.000        0.000      90.000
    5.000       5.446        1.540       -0.000        0.000      90.000
    5.500       6.219        1.550       -0.000        0.000      90.000
    6.000       6.995        1.556       -0.000        0.000      90.000
    6.500       7.774        1.559       -0.000        0.000      90.000
    7.000       8.555        1.561       -0.000        0.000      90.000
    7.500       9.336        1.563       -0.000        0.000      90.000
    8.000      10.117        1.563       -0.000        0.000      90.000
    8.500      10.899        1.564       -0.000        0.000      90.000
    9.000      11.681        1.564       -0.000        0.000      90.000
    9.500      12.463        1.564       -0.000        0.000      90.000
    9.530      12.510        1.564       -0.000        0.000      90.000
Accumulated transverse movement   -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang        Angle
                             Vel         Vel          Vel
    (sec)       (m)          (m/s)       (m/s)        (rad/s)    (deg)
    --------    --------     --------    --------     --------   -------
    0.000       0.000        1.564       -0.000        0.000      90.000
    0.100       0.100        0.140        0.003       -0.009      89.991
    0.105       0.100        0.041       -0.003        0.008      89.993
```

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.509   metres
Area exposed: 1.753   sq m   (77% of total)
Volume exposed: 0.2283 cu m   (89% of total)

```
**************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #14 Core #9     Date,Time: 06-22-2000     09:39:43
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                      (kg)                  294.835
Apparent mass in water    (kg)                  31.873
Overall length            (m)                   .8763
Maximum diameter          (m)                   .6096
Length of taper on base   (m)                   0
Minimum taper diameter    (m)                   .6096
Distance of CM from centre (m)                  0
External surface area    (sq m)                 2.262
Volume of mine           (cu m)                 0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE9
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------   ----------------  --------------------
    1             .02              1842               1880
    2             .04              1922               16550
    3             .06              1936               21220
    4             .08              1941               16980
    5             .1               2034               18920
    6             .14              2001               13900
    7             .18              1922               20600
    8             .22              1930               23220
    9             5                1930               23220
```

WATER PHASE

```
--------------------------------------------------------------------------
   Time        Depth        Vert         Horiz        Ang          Angle
                            Vel          Vel          Vel
   (sec)        (m)         (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
   0.000       0.000        0.000        0.000        0.000       90.000
   0.510       0.089        0.335       -0.000        0.000       90.000
   1.010       0.330        0.617       -0.000        0.000       90.000
   1.510       0.709        0.893       -0.000        0.000       90.000
   2.010       1.216        1.117       -0.000        0.000       90.000
   2.510       1.818        1.278       -0.000        0.000       90.000
   3.010       2.486        1.386       -0.000        0.000       90.000
   3.510       3.198        1.455       -0.000        0.000       90.000
   4.010       3.938        1.498       -0.000        0.000       90.000
   4.500       4.679        1.524       -0.000        0.000       90.000
   5.000       5.446        1.540       -0.000        0.000       90.000
   5.500       6.219        1.550       -0.000        0.000       90.000
   6.000       6.995        1.556       -0.000        0.000       90.000
   6.500       7.774        1.559       -0.000        0.000       90.000
   7.000       8.555        1.561       -0.000        0.000       90.000
   7.500       9.336        1.563       -0.000        0.000       90.000
   8.000      10.117        1.563       -0.000        0.000       90.000
   8.500      10.899        1.564       -0.000        0.000       90.000
   9.000      11.681        1.564       -0.000        0.000       90.000
   9.500      12.463        1.564       -0.000        0.000       90.000
   9.530      12.510        1.564       -0.000        0.000       90.000
```
Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

```
--------------------------------------------------------------------------
   Time        Depth        Vert         Horiz        Ang          Angle
                            Vel          Vel          Vel
   (sec)        (m)         (m/s)        (m/s)        (rad/s)      (deg)
  --------    --------     --------     --------     --------     -------
   0.000       0.000        1.564       -0.000        0.000       90.000
   0.103       0.116        0.516        0.001       -0.002       89.993
   0.141       0.126        0.023        0.003       -0.009       89.993
```

BURIAL RESULT:

Depth of burial: 0.126   metres

Height protruding: 0.484   metres
Area exposed: 1.671   sq m   (74% of total)
Volume exposed: 0.2177 cu m   (85% of total)

138

```
*********************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL       ******
    DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #14 Core #10     Date,Time: 06-22-2000      09:40:19
Speed mode: Rigorous
---------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                      (kg)                   294.835
Apparent mass in water    (kg)                    31.873
Overall length             (m)                     .8763
Maximum diameter           (m)                     .6096
Length of taper on base    (m)                    0
Minimum taper diameter     (m)                     .6096
Distance of CM from centre (m)                    0
External surface area    (sq m)                   2.262
Volume of mine           (cu m)                   0.256


---------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE10
  Layer #    Depth to base(m)   Density (kg/m^3)   Bearing strength(Pa)
  ------    ---------------   ----------------   --------------------
     1           0                 0                    0
     2           .02              1862                 1800
     3           .04              1870                24720
     4           .06              1862                32430
     5           .08              1905                23950
     6           .1               1879                31280
     7           .14              1876                29160
     8           .18              1903                20600
     9          5                 1903                20600
```

WATER PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time (sec)	Depth (m)	Vert Vel (m/s)	Horiz Vel (m/s)	Ang Vel (rad/s)	Angle (deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.100	0.100	0.140	0.003	-0.009	89.991
0.105	0.100	0.041	-0.003	0.008	89.993

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.509   metres
Area exposed: 1.753   sq m   (77% of total)
Volume exposed: 0.2283 cu m   (89% of total)

```
*******************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #15 Core #9      Date,Time: 06-22-2000      09:42:37
Speed mode: Rigorous
-------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)                    294.835
Apparent mass in water      (kg)                    31.873
Overall length              (m)                     .8763
Maximum diameter            (m)                     .6096
Length of taper on base     (m)                     0
Minimum taper diameter      (m)                     .6096
Distance of CM from centre  (m)                     0
External surface area    (sq m)                     2.262
Volume of mine           (cu m)                     0.256


-------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12
```

Sediment characteristics: CORE9

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1842	1880
2	.04	1922	16550
3	.06	1936	21220
4	.08	1941	16980
5	.1	2034	18920
6	.14	2001	13900
7	.18	1922	20600
8	.22	1930	23220
9	5	1930	23220

WATER PHASE

```
--------------------------------------------------------------------
   Time        Depth       Vert        Horiz        Ang        Angle
                           Vel         Vel          Vel
   (sec)        (m)        (m/s)       (m/s)        (rad/s)    (deg)
 --------    --------    --------    --------    --------    -------
   0.000       0.000       0.000       0.000       0.000      90.000
   0.510       0.089       0.335      -0.000       0.000      90.000
   1.010       0.330       0.617      -0.000       0.000      90.000
   1.510       0.709       0.893      -0.000       0.000      90.000
   2.010       1.216       1.117      -0.000       0.000      90.000
   2.510       1.818       1.278      -0.000       0.000      90.000
   3.010       2.486       1.386      -0.000       0.000      90.000
   3.510       3.198       1.455      -0.000       0.000      90.000
   4.010       3.938       1.498      -0.000       0.000      90.000
   4.500       4.679       1.524      -0.000       0.000      90.000
   5.000       5.446       1.540      -0.000       0.000      90.000
   5.500       6.219       1.550      -0.000       0.000      90.000
   6.000       6.995       1.556      -0.000       0.000      90.000
   6.500       7.774       1.559      -0.000       0.000      90.000
   7.000       8.555       1.561      -0.000       0.000      90.000
   7.500       9.336       1.563      -0.000       0.000      90.000
   8.000      10.117       1.563      -0.000       0.000      90.000
   8.500      10.899       1.564      -0.000       0.000      90.000
   9.000      11.681       1.564      -0.000       0.000      90.000
   9.500      12.463       1.564      -0.000       0.000      90.000
   9.530      12.510       1.564      -0.000       0.000      90.000
```
Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

```
--------------------------------------------------------------------
   Time        Depth       Vert        Horiz        Ang        Angle
                           Vel         Vel          Vel
   (sec)        (m)        (m/s)       (m/s)        (rad/s)    (deg)
 --------    --------    --------    --------    --------    -------
   0.000       0.000       1.564      -0.000       0.000      90.000
   0.103       0.116       0.516       0.001      -0.002      89.993
   0.141       0.126       0.023       0.003      -0.009      89.993
```

BURIAL RESULT:

Depth of burial: 0.126 metres

Height protruding: 0.484 metres
Area exposed: 1.671 sq m   (74% of total)
Volume exposed: 0.2177 cu m   (85% of total)

```
************************************************************
******        NCSC/DSE IMPACT BURIAL PREDICTION MODEL        ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #15 Core #10     Date,Time: 06-22-2000     09:43:19
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length              (m)               .8763
Maximum diameter            (m)               .6096
Length of taper on base     (m)               0
Minimum taper diameter      (m)               .6096
Distance of CM from centre  (m)               0
External surface area    (sq m)               2.262
Volume of mine           (cu m)               0.256


-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12
```

Sediment characteristics: CORE10

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	0	0	0
2	.02	1862	1800
3	.04	1870	24720
4	.06	1862	32430
5	.08	1905	23950
6	.1	1879	31280
7	.14	1876	29160
8	.18	1903	20600
9	5	1903	20600

WATER PHASE

```
--------------------------------------------------------------------------
   Time         Depth        Vert        Horiz        Ang        Angle
                             Vel         Vel          Vel
  (sec)          (m)         (m/s)       (m/s)       (rad/s)     (deg)
 ---------    ---------    ---------   ---------    ---------   -------
   0.000        0.000        0.000        0.000       0.000      90.000
   0.510        0.089        0.335       -0.000       0.000      90.000
   1.010        0.330        0.617       -0.000       0.000      90.000
   1.510        0.709        0.893       -0.000       0.000      90.000
   2.010        1.216        1.117       -0.000       0.000      90.000
   2.510        1.818        1.278       -0.000       0.000      90.000
   3.010        2.486        1.386       -0.000       0.000      90.000
   3.510        3.198        1.455       -0.000       0.000      90.000
   4.010        3.938        1.498       -0.000       0.000      90.000
   4.500        4.679        1.524       -0.000       0.000      90.000
   5.000        5.446        1.540       -0.000       0.000      90.000
   5.500        6.219        1.550       -0.000       0.000      90.000
   6.000        6.995        1.556       -0.000       0.000      90.000
   6.500        7.774        1.559       -0.000       0.000      90.000
   7.000        8.555        1.561       -0.000       0.000      90.000
   7.500        9.336        1.563       -0.000       0.000      90.000
   8.000       10.117        1.563       -0.000       0.000      90.000
   8.500       10.899        1.564       -0.000       0.000      90.000
   9.000       11.681        1.564       -0.000       0.000      90.000
   9.500       12.463        1.564       -0.000       0.000      90.000
   9.530       12.510        1.564       -0.000       0.000      90.000
```
Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

```
--------------------------------------------------------------------------
   Time         Depth        Vert        Horiz        Ang        Angle
                             Vel         Vel          Vel
  (sec)          (m)         (m/s)       (m/s)       (rad/s)     (deg)
 ---------    ---------    ---------   ---------    ---------   -------
   0.000        0.000        1.564       -0.000       0.000      90.000
   0.100        0.100        0.140        0.003      -0.009      89.991
   0.105        0.100        0.041       -0.003       0.008      89.993
```

BURIAL RESULT:

Depth of burial: 0.100   metres

Height protruding: 0.509   metres
Area exposed: 1.753   sq m   (77% of total)

Volume exposed: 0.2283 cu m   (89% of total)

144

```
****************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #16 Core #11     Date,Time: 06-22-2000     09:53:17
Speed mode: Rigorous
------------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                        (kg)                    294.835
Apparent mass in water      (kg)                    31.873
Overall length              (m)                     .8763
Maximum diameter            (m)                     .6096
Length of taper on base     (m)                     0
Minimum taper diameter      (m)                     .6096
Distance of CM from centre  (m)                     0
External surface area    (sq m)                     2.262
Volume of mine           (cu m)                     0.256


------------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12
```

Sediment characteristics: CORE11

Layer #	Depth to base(m)	Density (kg/m^3)	Bearing strength(Pa)
1	.02	1962	8900
2	.04	1902	16120
3	.06	1947	15330
4	.08	1932	16980
5	.1	1971	14950
6	.14	2069	12380
7	.18	1976	16120
8	.22	1851	13580
9	.26	1886	15330
10	5	1886	15330

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.101	0.115	0.577	0.001	-0.003	89.995
0.150	0.128	0.004	0.005	-0.014	89.987

BURIAL RESULT:

Depth of burial: 0.128 metres

Height protruding: 0.482 metres
Area exposed: 1.665 sq m   (74% of total)
Volume exposed: 0.2169 cu m   (85% of total)

```
*************************************************************************
******          NCSC/DSE IMPACT BURIAL PREDICTION MODEL          ******
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #17 Core #12     Date,Time: 06-22-2000     09:54:41
Speed mode: Rigorous
-------------------------------------------------------------------
Mine characteristics,       55GALDRM

Mass                      (kg)                    294.835
Apparent mass in water    (kg)                    31.873
Overall length            (m)                     .8763
Maximum diameter          (m)                     .6096
Length of taper on base   (m)                     0
Minimum taper diameter    (m)                     .6096
Distance of CM from centre (m)                    0
External surface area    (sq m)                   2.262
Volume of mine            (cu m)                  0.256


-------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)               0
Horiz vel (rightward pos)                  0
Angle(0 vertical,90 horizontal)            90
Rotation rate(rad/sec cl'wise)             0
Water depth (m):                           12.497
Temperature (deg C):                       12

Sediment characteristics:  CORE12
 Layer #     Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------      --------------    ----------------  --------------------
    1            .02               1914               7960
    2            .04               2002               15330
    3            .06               1913               13900
    4            .08               1910               14240
    5            .1                1921               15720
    6            .14               1889               16550
    7            .18               1895               18410
    8            .22               1917               26360
    9            5                 1917               26360
```

WATER PHASE

```
---------------------------------------------------------------------
   Time       Depth       Vert       Horiz       Ang        Angle
                          Vel         Vel        Vel
   (sec)       (m)       (m/s)       (m/s)      (rad/s)     (deg)
  --------   --------   --------   --------    --------    -------
   0.000      0.000      0.000      0.000       0.000      90.000
   0.510      0.089      0.335     -0.000       0.000      90.000
   1.010      0.330      0.617     -0.000       0.000      90.000
   1.510      0.709      0.893     -0.000       0.000      90.000
   2.010      1.216      1.117     -0.000       0.000      90.000
   2.510      1.818      1.278     -0.000       0.000      90.000
   3.010      2.486      1.386     -0.000       0.000      90.000
   3.510      3.198      1.455     -0.000       0.000      90.000
   4.010      3.938      1.498     -0.000       0.000      90.000
   4.500      4.679      1.524     -0.000       0.000      90.000
   5.000      5.446      1.540     -0.000       0.000      90.000
   5.500      6.219      1.550     -0.000       0.000      90.000
   6.000      6.995      1.556     -0.000       0.000      90.000
   6.500      7.774      1.559     -0.000       0.000      90.000
   7.000      8.555      1.561     -0.000       0.000      90.000
   7.500      9.336      1.563     -0.000       0.000      90.000
   8.000     10.117      1.563     -0.000       0.000      90.000
   8.500     10.899      1.564     -0.000       0.000      90.000
   9.000     11.681      1.564     -0.000       0.000      90.000
   9.500     12.463      1.564     -0.000       0.000      90.000
   9.530     12.510      1.564     -0.000       0.000      90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
---------------------------------------------------------------------
   Time       Depth       Vert       Horiz       Ang        Angle
                          Vel         Vel        Vel
   (sec)       (m)       (m/s)       (m/s)      (rad/s)     (deg)
  --------   --------   --------   --------    --------    -------
   0.000      0.000      1.564     -0.000       0.000      90.000
   0.100      0.117      0.617      0.002      -0.005      89.996
   0.145      0.130      0.041     -0.004       0.010      89.995
```

BURIAL RESULT:

Depth of burial: 0.130   metres

Height protruding: 0.479   metres
Area exposed: 1.657   sq m   (73% of total)
Volume exposed: 0.2157 cu m   (84% of total)

```
*****************************************************************
******         NCSC/DSE IMPACT BURIAL PREDICTION MODEL         ******
      DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #16 Core #12     Date,Time: 06-22-2000     09:53:52
Speed mode: Rigorous
-----------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                        (kg)              294.835
Apparent mass in water      (kg)              31.873
Overall length               (m)              .8763
Maximum diameter             (m)              .6096
Length of taper on base      (m)              0
Minimum taper diameter       (m)              .6096
Distance of CM from centre  (m)              0
External surface area    (sq m)              2.262
Volume of mine           (cu m)              0.256


-----------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)            0
Horiz vel (rightward pos)               0
Angle(0 vertical,90 horizontal)         90
Rotation rate(rad/sec cl'wise)          0
Water depth (m):                        12.497
Temperature (deg C):                    12

Sediment characteristics:  CORE12
 Layer #    Depth to base(m)  Density (kg/m^3)  Bearing strength(Pa)
 ------     ---------------   ----------------  --------------------
    1            .02            1914               7960
    2            .04            2002               15330
    3            .06            1913               13900
    4            .08            1910               14240
    5            .1             1921               15720
    6            .14            1889               16550
    7            .18            1895               18410
    8            .22            1917               26360
    9            5              1917               26360
```

WATER PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang        Angle
                             Vel          Vel         Vel
   (sec)         (m)        (m/s)        (m/s)      (rad/s)      (deg)
 ---------    ---------    ---------    ---------    ---------    -------
   0.000        0.000        0.000        0.000        0.000      90.000
   0.510        0.089        0.335       -0.000        0.000      90.000
   1.010        0.330        0.617       -0.000        0.000      90.000
   1.510        0.709        0.893       -0.000        0.000      90.000
   2.010        1.216        1.117       -0.000        0.000      90.000
   2.510        1.818        1.278       -0.000        0.000      90.000
   3.010        2.486        1.386       -0.000        0.000      90.000
   3.510        3.198        1.455       -0.000        0.000      90.000
   4.010        3.938        1.498       -0.000        0.000      90.000
   4.500        4.679        1.524       -0.000        0.000      90.000
   5.000        5.446        1.540       -0.000        0.000      90.000
   5.500        6.219        1.550       -0.000        0.000      90.000
   6.000        6.995        1.556       -0.000        0.000      90.000
   6.500        7.774        1.559       -0.000        0.000      90.000
   7.000        8.555        1.561       -0.000        0.000      90.000
   7.500        9.336        1.563       -0.000        0.000      90.000
   8.000       10.117        1.563       -0.000        0.000      90.000
   8.500       10.899        1.564       -0.000        0.000      90.000
   9.000       11.681        1.564       -0.000        0.000      90.000
   9.500       12.463        1.564       -0.000        0.000      90.000
   9.530       12.510        1.564       -0.000        0.000      90.000
Accumulated transverse movement    -0.0 m
```

SEDIMENT PHASE

```
--------------------------------------------------------------------------
    Time        Depth        Vert        Horiz        Ang        Angle
                             Vel          Vel         Vel
   (sec)         (m)        (m/s)        (m/s)      (rad/s)      (deg)
 ---------    ---------    ---------    ---------    ---------    -------
   0.000        0.000        1.564       -0.000        0.000      90.000
   0.100        0.117        0.617        0.002       -0.005      89.996
   0.145        0.130        0.041       -0.004        0.010      89.995
```

BURIAL RESULT:

Depth of burial: 0.130   metres

Height protruding: 0.479   metres
Area exposed: 1.657   sq m   (73% of total)
Volume exposed: 0.2157 cu m   (84% of total)

150

```
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* * * * * *          NCSC/DSE IMPACT BURIAL PREDICTION MODEL              * * * * * *
     DOTSE development version IMPACTD1 with 100 Layers,20 March 1997

Run name: Drop #17 Core #11     Date,Time: 06-22-2000      09:55:11
Speed mode: Rigorous
----------------------------------------------------------------------
Mine characteristics,        55GALDRM

Mass                      (kg)                  294.835
Apparent mass in water    (kg)                  31.873
Overall length             (m)                  .8763
Maximum diameter           (m)                  .6096
Length of taper on base    (m)                  0
Minimum taper diameter     (m)                  .6096
Distance of CM from centre (m)                  0
External surface area   (sq m)                  2.262
Volume of mine          (cu m)                  0.256


----------------------------------------------------------------------
RELEASE CONDITIONS
Vert vel (downward positive)              0
Horiz vel (rightward pos)                 0
Angle(0 vertical,90 horizontal)           90
Rotation rate(rad/sec cl'wise)            0
Water depth (m):                          12.497
Temperature (deg C):                      12

Sediment characteristics:  CORE11
 Layer #     Depth to base(m)   Density (kg/m^3)  Bearing strength(Pa)
 ------      ---------------    ----------------  --------------------
    1             .02               1962                 8900
    2             .04               1902                16120
    3             .06               1947                15330
    4             .08               1932                16980
    5             .1                1971                14950
    6             .14               2069                12380
    7             .18               1976                16120
    8             .22               1851                13580
    9             .26               1886                15330
   10            5                  1886                15330
```

WATER PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	0.000	0.000	0.000	90.000
0.510	0.089	0.335	-0.000	0.000	90.000
1.010	0.330	0.617	-0.000	0.000	90.000
1.510	0.709	0.893	-0.000	0.000	90.000
2.010	1.216	1.117	-0.000	0.000	90.000
2.510	1.818	1.278	-0.000	0.000	90.000
3.010	2.486	1.386	-0.000	0.000	90.000
3.510	3.198	1.455	-0.000	0.000	90.000
4.010	3.938	1.498	-0.000	0.000	90.000
4.500	4.679	1.524	-0.000	0.000	90.000
5.000	5.446	1.540	-0.000	0.000	90.000
5.500	6.219	1.550	-0.000	0.000	90.000
6.000	6.995	1.556	-0.000	0.000	90.000
6.500	7.774	1.559	-0.000	0.000	90.000
7.000	8.555	1.561	-0.000	0.000	90.000
7.500	9.336	1.563	-0.000	0.000	90.000
8.000	10.117	1.563	-0.000	0.000	90.000
8.500	10.899	1.564	-0.000	0.000	90.000
9.000	11.681	1.564	-0.000	0.000	90.000
9.500	12.463	1.564	-0.000	0.000	90.000
9.530	12.510	1.564	-0.000	0.000	90.000

Accumulated transverse movement   -0.0 m

SEDIMENT PHASE

Time	Depth	Vert Vel	Horiz Vel	Ang Vel	Angle
(sec)	(m)	(m/s)	(m/s)	(rad/s)	(deg)
0.000	0.000	1.564	-0.000	0.000	90.000
0.101	0.115	0.577	0.001	-0.003	89.995
0.150	0.128	0.004	0.005	-0.014	89.987

BURIAL RESULT:

Depth of burial: 0.128   metres

Height protruding: 0.482   metres
Area exposed: 1.665   sq m   (74% of total)

Volume exposed: 0.2169 cu m   (85% of total)

LIST OF REFERENCES

1. Arnone, R. A., and Bowen, Prediction model of the time history penetration of a cylinder through the air-water-sediment phases. NCSC TN 734-36. Naval Coastal Systems Center, Panama City, FL, 1980.

2. Thomson, E. T., and Emery, Data Analysis Methods in Physical Oceanography, 1998.

3. Taber, V. L., Environmental Sensitivity Study on Mine Impact Burial Prediction Model, *Master Thesis*, Naval Postgraduate School, Monterey, CA, 1999.

4. Casper, L. E., Halter, I. L., Powers, E. W., Selva, P. J., Steffens, T. W., and Willis, T. L., Knowledge-based warfare: the strategy for the next century. *Joint Force Quarterly*, Autumn, 81-89, 1996.

5. Greenwood, B., and Davis, R. A., Hydrodynamics and Sedimentation in Wave-dominated Coastal Environments, 1984.

6. Naval Mine Warfare Engineering Activity (NMWEA), U.S. Navy Mine Countermeasures Familiarizer. Naval Coastal Systems Center, Panama City, Fl, 1991.

7. Noorany, I., Laboratory Soil Properties. *Handbook for Marine Geotechnical Engineering*, edited by K. Rocker, Jr., Naval Civil Engineering Laboratory, Port Hueneme, CA, 3.1-3.19, 1985.

8. Satkowiak, L. J., Modified NCSC Impact Burial Prediction Model With Comparisons to Mine Drop Tests. NCSC TN 486-88. Naval Coastal Systems Center, Panama City, FL. Technical Note 934, 1988.

9. Satkowiak, L. J., User's Guide For the Modified Impact Burial Prediction Model. NCSC TN 884-87. Naval Coastal Systems Center, Panama City, FL. 1987.

10. Yalin, M. S., Mechanics of Sediment Transport, (1925-), 1996.

11. Stanley, E. M., Viscosity of Sea Water at Moderate Temperatures and Pressures, *Journal of Geophysical Research*, 74, 3415-3420, 1969.

12. Fredsoe, J., and Deigaard, R., Mechanics of Coastal Sediment Transport, 1992.

13. Chu, P. C., E. Gottshall, and T.E. Halwachs, Environmental Effects on naval Warfare Simulations, Institute of Joint Warfare Analysis, Naval Postgraduate School, Technical Report, NPS-IJWA-98-006, pp.33, 1998a.

14. Chu, P.C., E. Gottshall, and T.E. Halwachs, A Meteorological and Oceanographic (METOC) support for determining safe current in magnetic sea mine sweeping, The Third International Symposium on Technology and the Mine Problem (CD-ROM), 6 pages, 1998b.

15. Chu, P.C., V.I. Taber, and S.D. Haeger, A Mine Impact Burial Model Sensitivity Study, Institute of Joint Warfare Analysis, Naval Postgraduate School, Technical Report, NPS-IJWA-00-003, pp.48, 2000a.

16. Chu, P.C., V.I. Taber, and S.D. Haeger, An Environmental Sensitivity Study on Mine Impact Burial Prediction Model, Proceedings on The Fourth International Symposium on Technology and the Mine Problem, 10 pages, 2000b.

17. Hamilton, E.L., and Bachman, R.T., sound velocity and related properties of marine sediments, J. Acoust. Soc. Am., 72(6), 1891-1904, 1982.

18. Hayter, E.J., Estuarine sediment bed model. Estuarine Cohesive Sediment Dynamics, edited by A.J. Mehta, pp. 326-359, Springer-Verlag, New York, 1986.

19. Krone, R.B., a study of rheological properties of estuarine sediments. Technical Bulletin No. 7, Committee of Tidal Hydraulics. U.S. Army Corps of Engineers. Vicksburg, MS, 1963.

20. Von Mises, R., Theory of Flight, Dover Publ., New York, 1959.

21. Mulhearn, P.J., Experiments on mine burial on impact-Sydney Harbour. U.S. Navy J. of Underwater Acoustics, 43, 1271-1281, 1992.

22. Naval Surface Warfare Center, Mine Countermeasures Commander's Tactical Decision Aid (MCM-CTDA). Coastal Systems Station, Dahlgren Division.

23. Monterey Bay National Marine Sanctuary Site Characterization. http://www.mbnms.nos.noaa.gov/sitechar/main.html

INITIAL DISTRIBUTION LIST

11. LT Timothy B. Smith 1
229 Orange Avenue #6
Coronado, CA 92118

12. COMNAVMINWARCOM 1
325 5th Street SE
Corpus Christi, TX 78419-5032

13. SPAWARSYSCEN 1
PMW185 METOC Systems
4301 Pacific Highway
OT-1 Room 1187
San Diego, CA 92110-3127